



RH TT DUCT

Relative Humidity (RH), Temperature Transmitter (TT)

The ACI Relative Humidity with Temperature Transmitter Duct Series utilizes a thermoset polymer capacitive sensing element with a factory fitted hydrophobic filter to improve its moisture resistance. The sensing elements multilayer construction also provides excellent resistance in applications where dust, dirt, oils and common environmental chemicals are found. The RH duct sensors include on board DIP switches which allow the user to select the desired output signal and can be powered by AC or DC power sources. Single point field calibration can be performed by using the increment and decrement calibration DIP switches to adjust your curve up or down in +/- 0.5% increments with each toggle of the corresponding switches. These enhancements provide increased flexibility and outstanding long-term reliability without the need to replace the sensors in

the field. Duct configurations feature either a NEMA 4X or NEMA 3R enclosure and a conformally coated circuit board for increased moisture resistance in high humidity environments. NIST Calibration Certificates are available for all RH TTM part series.

Applications: Humidification, Dehumidification, Supply and Return RH sensors, Economizers, Clean Rooms, Data Centers, Process Control

The ACI RH TT Duct is covered by ACI's Five (5) Year Limited Warranty. The warranty can be found in the front of ACI's Sensors & Transmitters catalog, as well as on ACI's website, www.workaci.com.

PRODUCT SPECIFICATIONS

RH Supply Voltage (Reverse Polarity Protected):	4-20 mA: 250 Ohm Load: 15 - 40 VDC / 18 - 28 VAC 500 Ohm Load: 18 - 40 VDC / 18 - 28 VAC
RH Supply Current (VA):	0-5 VDC: 12 - 40 VDC / 18 - 28 VAC 0-10 VDC: 18 - 40 VDC / 18 - 28 VAC
RH Output Load Resistance:	Voltage Output: 8 mA maximum (0.32 VA) Current Output: 24 mA maximum (0.83 VA)
RH Output Signal:	4-20 mA: 700 Ohms maximum 0-5 VDC or 0-10 VDC: 4K Ohms Minimum
RH Accuracy @ 77°F (25°C):	2-wire: 4 - 20 mA (Factory Default) 3-wire: 0-5 or 0-10 VDC & 4 - 20 mA (Field Selectable)
RH Measurement Range:	+/- 1% over 20% RH Range between 20 to 90% +/- 2%, 3%, or 5% from 10 to 95%
Operating RH Range:	0-100%
Operating Temperature Range:	0 to 95% RH, non-condensing (Conformally Coated PCB's)
Storage Temperature Range:	-40 to 140°F (-40 to 60°C)
RH Stability Repeatability Sensitivity:	-40 to 149°F (-40 to 65°C)
RH Response Time (T63):	Less than 2% drift / 5 years 0.5% RH 0.1% RH
RH Sensor Type:	20 Seconds Typical
RH Transmitter Stabilization Time:	Capacitive with Hydrophobic Filter
RH Connections Wire Size:	30 Minutes (Recommended time before doing accuracy verification)
RH Terminal Block Torque Rating:	Screw Terminal Blocks (Polarity Sensitive) 16 (1.31 mm ²) to 26 AWG (0.129 mm ²)
RH NIST Test Points:	4.43 to 5.31 lb-in (0.5 to 0.6 Nm)
	Default Test Points: 3 Points (20%, 50% & 80%) or 5 Points (20%, 35%, 50%, 65% & 80%)
	1% NIST Test Points: 5 Points within selected 20% Range (ie. 30%-50% are 30, 35, 40, 45 & 50)
TT Supply Voltage:	+8.5 to 32 VDC (Reverse Polarity Protected)
Supply Current:	25 mA minimum
	250 Ohm Load: +13.5 to 32 VDC 500 Ohm Load: +18.5 to 32 VDC
TT Maximum Load Resistance:	(Terminal Voltage - 8.5 V) / 0.020 A
TT Output Signals:	Current Output: 4-20 mA (2-Wire Loop Powered) Voltage Output: 1-5 VDC/2-10 VDC (3-Wire)
TT Calibrated Accuracy Linearity :	Temperature Spans < 500°F (260°C): +/- 0.2% Temp Spans > 500°F (260°C): +/- 0.5%
TT Temperature Drift ²:	Temperature Spans < 100°F (38°C): +/- 0.04%/°F Temp Spans > 100°F (38°C): +/- 0.02%/°F
TTM100/TTM1K Certification Points:	3 Point NIST: 20%, 50%, 80% of span 5 Point NIST: 20%, 35%, 50%, 65%, 80% of span
TT Warm Up Time:	10 Minutes +/- 0.1%
Warm Up Drift:	-40 to 185°F (-40 to 85°C)
Transmitter Operating Temperature/RH Range:	0 to 90% RH, non-condensing
Platinum RTD (PTC) Number Wires Wire Colors:	Two A/TT100/TTM100 Series: Brown/Brown A/TT1K/TTM1K Series: Black/Black
Platinum RTD Sensor Output @ 32°F (0°C):	A/TT100/TTM100 Series: 100 Ohms Nominal A/TT1K/TTM1K Series: 1000 Ohms Nominal
Platinum RTD Tolerance Class Accuracy:	+/- 0.06% Class A Tolerance Formula: +/- °C = (0.15°C + (0.002 * t))
	where t is the absolute value of Temperature above or below 0°C in °C
Platinum RTD Sensor Stability:	+/- 0.03% after 1000 Hours @ 572°F (300°C)
Platinum RTD Response Time (63% Step Change):	8 Seconds nominal
Enclosure Specifications (Material, Flammability, Temperature, NEMA/IP Rating):	"-4X" Enclosure: Polystyrene Plastic; UL94-V2; -40 to 158°F (-40 to 70°C); NEMA 4X (IP 66)
Sensing Tube Dimensions:	"-BB" Enclosure: Aluminum, -40 to 239°F (-40 to 110°C); NEMA 3R (IP10)
Tube Material:	7.20" (182.88 mm) x 0.840" (21.34 mm)
Product Dimensions (L x W x D):	Slotted PVC without filter
Product Weight:	See drawings on back of data sheet
Agency Approvals:	A/RHx-TT-D-4X Series: 0.58 lbs. (0.263 kg)
	RoHS2, WEEE




Note 1: A Transmitter is calibrated at 71°F (22°C) Nominal | **Note 2:** Temperature Drift is referenced to 71°F nominal calibration temperature








DIMENSIONAL DRAWING

D-4X [NEMA 4X]



D-BB [NEMA 3R]



Front View

Right View

Top View

CUSTOM ORDERING

Model # Example: A/ RH2 TT1K D-4X 2 0-200°F

MODEL #

A. Sensor Series No Selection Required	A/
B. Accuracy Select One (1)	RH1 = +/-1% (Specify a 20% Range between 20 to 90% RH) RH2 = +/-2% RH3 = +/-3% RH5 = +/-5%
C. Model Series Select One (1)	TT100 = 100 Ohms TTM100 = Matched 100 Ohms (Specify 3 or 5 Point NIST) TT1K = 1K Ohms TTM1K = Matched 1K Ohms (Specify 3 or 5 Point NIST)
D. Configuration Select One (1)	D-4X = Duct (NEMA 4X Enclosure) D-BB = Duct (NEMA 3R Enclosure)
E. Transmitter Output Select One (1)	4 = 4 to 20 mA 1 = 1 to 5 VDC* 2 = 2 to 10 VDC*
F. Calibrated Span	Specify Span in °F or °C (Best Accuracy in 100°F Increments)

Note*: A Temperature Transmitter Output of 1-5 VDC or 2-10 VDC would have a RH Output of 0-5 VDC or 0-10 VDC

ACCESSORIES ORDERING [NIST]

Model # Example: NIST RH CERT

Model #	Description
---- (Default)	TTM Calibration Certificate (3 Point NIST)
NIST TTM CERT - 5PT.	TTM Calibration Certificate (5 Point NIST)
NIST RH CERT	TTM Calibration Certificate (Specify 3 Point or 5 Point NIST)

Note: When Ordering NIST Certificates, Please add an additional line item under the corresponding A/RHx-TTMxx-D Model Number