



## Q6/B6 SERIES

### Toxic/Combustible Gas Transmitter

The Q6/B6 Toxic/Combustible Gas Detectors use various sensing technologies to detect a wide assortment of gases. These units are housed in a NEMA 4X rated plastic enclosure that will meet a wide variety of applications. The combo unit consists of a main unit (Carbon Monoxide only) with an LCD, LED status indication, 3 user configurable relays and a remote sensing unit (various gas types available) for installation at high or low elevations based on the density of the gas being detected. The main and remote unit gas concentrations levels are both displayed on the main unit's LCD. This series also features a sensor module that can be easily replaced by removing a couple of screws and unplugging the existing module before inserting the new factory calibrated sensing module. All units should be verified for proper functionality and calibration once the replacement sensor module has been reinstalled. A user selectable password can be used to protect the system integrity. The Q6 can be used as a stand-alone

controller or in conjunction with one of our Q4C, M-Controller or Q-Controllers using the proprietary RS-485 Optomux communication protocol. Calibration gases and a 0.2 to 1 liter/minute flow limiting gas regulator are not available through ACI and should be purchased through your local gas supply company or on-line companies such as Portagas®(Praxair®, Inc.) or Mesa Specialty Gases®. ACI also offers a full line of horns and strobes that can be used with the gas detectors or building management system to alert building occupants of an alarm condition.

It is your responsibility to ensure that the Q6/B6 Series will meet all of your applicable Federal, State, Provincial and Local Health and Safety laws and regulations before using these products.

**Applications:** Mechanical Rooms, Warehouses, Refrigeration Plants, Industrial Plants, Process Monitoring, Leak Detection, Parking Garages, Auto/Truck Maintenance Facilities, Oil and Gas Industry

**The Q6/B6 Series Gas Transmitters are covered by ACI's Two (2) Year Limited Warranty against defects in material and workmanship from the date of shipment with the exception of the Sensor Modules (Electrochemical/Toxic: Six Months and Catalytic/Combustible: One Year). The warranty can be found in the front of ACI's Sensors & Transmitters catalog, as well as on ACI's website, [www.workaci.com](http://www.workaci.com).**

## PRODUCT SPECIFICATIONS


<b>Supply Voltage [Q6]:</b>	<b>VDC Supply Voltage:</b> 24 VDC nominal (+18 to 30 VDC) (AC Power must not be grounded)
	<b>VAC Supply Voltage:</b> 24 VAC nominal (+15 to 24 VAC, AC Power must not be grounded)
<b>Supply Voltage [B6]:</b>	<b>VDC Supply Voltage:</b> 24 VDC nominal (+18 to 30 VDC) (AC Power can be grounded or non-grounded)
	<b>VAC Supply Voltage:</b> 24 VAC nominal (+15 to 24 VAC, AC Power must not be grounded)
<b>Fuse Protection:</b>	0.750A Polyswitch; (Resets after fault is cleared & power to circuit is removed)
<b>Supply Current   Power Consumption:</b>	0.3A maximum   8.4 VA
<b>Communication Protocols:</b>	<b>Q6 Communication Protocols:</b> RS-485 Modbus RTU / OptoMux (Proprietary QEL Controller Protocol)
	<b>B6 Communication Protocols:</b> RS-485 Serial BACnet™ MS/TP (Master and Slave; Default: Master)
<b>Q6 Communication Baud Rates [Q6]:</b>	1200, 2400, 4800, 9600, 14400, 19200, 28800, 38400, 57600, 76800 Bits/Second (Default: 4800)
<b>B6 Communication Baud Rates [B6]:</b>	9600, 19200, 38400, 76800 Bits/Second (Default: 38400)
<b>Factory Calibration Range:</b>	See Gas Sensor Selection & Specification Table on back of data sheet
<b>Display:</b>	LCD Graphic Display with backlight (Displays: TWA, STEL and Concentration)
<b>Keypad:</b>	Three Capacitive Touch sensing keys
<b>Relays   Contact Type   Relay Contact Ratings:</b>	Three   SPDT (Form C) Dry Contacts   1.0A max. @ 30 VDC or 0.3A max. @ 125 VAC (Resistive Loads)
<b>Relay Life Expectancy:</b>	<b>Mechanical:</b> 50,000,000 operations minimum @ 36,000 operations/hour
	<b>Electrical:</b> 200,000 operations minimum @ rated load
<b>Status LEDs:</b>	Two Green LEDs (Tx/Rx Communication Status); Three Red LEDs (Relays 1, 2, & 3)
<b>Buzzer:</b>	80 dB at 3.94" (10 cm), 2700 Hz (3 Programmable Tones)
<b>Sensor Warm Up Time:</b>	24 Hours (Allow 24 hours before calibrating sensor after installation)
<b>Sensor Type:</b>	<b>Main:</b> Carbon Monoxide (CO)   <b>Remote:</b> See Gas Sensor Selection & Specification Table on back of data sheet
<b>Sensor Gas Types:</b>	Combustible, Toxic Gases/Oxygen Sensor & Infrared
<b>Coverage Area   Mounting Height:</b>	See Gas Sensor Selection & Specification Table on back of data sheet
<b>Sensor Life Expectancy:</b>	Toxic/Electrochemical Sensors: 2 to 3 Years, typical; Oxygen/Hydrogen Sensors: 18 months, typical
	Combustible/Catalytic: 3 to 5 years, typical; CO 7 years, typical
<b>Unit Shelf Life:</b>	<b>Electrochemical (Toxic) Sensors:</b> 6 months from date of purchase
	<b>Catalytic (Combustible) Sensors:</b> 1 year from date of purchase
<b>Replacement Sensor Modules:</b>	See additional on-line Product Literature or Contact ACI
<b>Recommended Maintenance:</b>	<b>Combustible Sensors:</b> Accuracy & Bump test every 3 months or as required by Code
	<b>Toxic Sensors:</b> Accuracy & Bump test every 6 months or as required by Code
<b>Enclosure Specifications (Material Type, Flammability, NEMA/IP Rating):</b>	Plastic Enclosure; Polycarbonate Lexan; UL94 V-0, NEMA 4, 4X, 12 and 13 (IP66)
<b>Enclosure Knockouts:</b>	¾" Knockouts (accepts ½" Conduit Fittings)
<b>Operating Temperature   Humidity:</b>	See Sensor Selection & Specification Table on back of data sheet   5 to 95% RH, non-condensing
<b>Operating Atmospheric Pressure:</b>	14.696 psi (1.0132 bar) +/- 10%
<b>Recommended Storage Temperature/Humidity:</b>	32 to 68°F (0 to 20°C)   5 to 95% RH, Non-Condensing
<b>Wiring Connections   Wire Size:</b>	De-pluggable Screw Terminal Blocks   16 to 24 AWG (0.2047 to 1.301 mm) Shielded Twisted Pair
<b>Communications Cable:</b>	Belden 9841 or Equivalent, 120 Ohms Input Impedance
<b>Terminal Block Torque Rating:</b>	0.37 ft-lb (0.502 Nm) Nominal

**Note:** When installed @ > 3000' above sea level, the gas transmitters must be verified for accuracy & re-calibrated as needed after installation





## DIMENSIONAL DRAWING



## SENSOR SELECTION AND SPECIFICATION

Gas Type	Gas Span Code	Combustible	Toxic	100% LEL <sup>1</sup> in % By Vol.	Measurement Range	Operating Temp °F (°C)	Square Feet ft² (m²)	Radius ft (m)	Mounting Height
Acetone	CH3CO-100L	•		2.6%	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Ammonia	NH3-100P		•	N/A	0 - 100 PPM	-22 to 122 (-30 to 50)	7500 (696.7)	49 (14.9)	High **
Ammonia	NH3-1000P		•	N/A	0 - 1000 PPM	-22 to 122 (-30 to 50)	7500 (696.7)	49 (14.9)	High **
Arsine	ASH3-1P		•	N/A	0 - 1 PPM	-4 to 104 (-20 to 40)	5000 (464.5)	40 (12.2)	Low **
Benzene	C6H6-100L	•		1.3%	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Iso-Butane	C4H10-100L	•		1.8%	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Butanol, n-Butane	BUTAN-100L	•		1.9%	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Carbon Dioxide	CO2-5000P	Infrared	Infrared	N/A	0 - 5000 PPM	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Mid **
Carbon Dioxide	CO2-5V	Infrared	Infrared	N/A	0 - 5% by Volume	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Mid **
Carbon Dioxide	CO2-20V	Infrared	Infrared	N/A	0 - 20% Volume	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Mid **
Carbon Dioxide	CO2-100V	Infrared	Infrared	N/A	0 - 100% Volume	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Mid **
Carbon Monoxide	CO-250P		•	N/A	0 - 250 PPM	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Mid **
Carbon Monoxide	CO-1000P		•	N/A	0 - 1000 PPM	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Mid **
Chlorine	CL2-5P			N/A	0 - 5 PPM	-4 to 122 (-20 to 50)	5000 (464.5)	40 (12.2)	Low **
Chlorine Dioxide	CLO2-2P		•	N/A	0 - 2 PPM	-4 to 122 (-20 to 50)	5000 (464.5)	40 (12.2)	Low **
Combustibles	GENL-100L	•		Specify Gas	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Gas Dependent
Diborane	B2H6-2P		•	N/A	0 - 2 PPM	-4 to 104 (-20 to 40)	5000 (464.5)	40 (12.2)	Mid **
Ethylene	C2H4-100L	•		2.7%	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Mid **
Ethylene Oxide	ETO-20P		•	N/A	0 - 20 PPM	-4 to 122 (-20 to 50)	5000 (464.5)	40 (12.2)	Low **
Germane	GEH4-2P		•	N/A	0 - 2 PPM	-4 to 104 (-20 to 40)	5000 (464.5)	40 (12.2)	Low **
Hydrogen	H2-1000P		•	N/A	0 - 1000 PPM	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	High **
Hydrogen	H2-2000P		•	N/A	0 - 2000 PPM	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	High **
Hydrogen	H2-100L	•		4.0%	0 - 100% LEL	-40 to 122 (-40 to 50)	7500 (696.7)	49 (14.9)	High **
Hydrogen Bromide	HBR-30P		•	N/A	0 - 30 PPM	-4 to 104 (-20 to 40)	5000 (464.5)	40 (12.2)	Low **
Hydrogen Chloride	HCL-30P		•	N/A	0 - 30 PPM	-4 to 122 (-20 to 50)	5000 (464.5)	40 (12.2)	Mid **
Hydrogen Cyanide	HCN-50P		•	N/A	0 - 50 PPM	-4 to 122 (-20 to 50)	5000 (464.5)	40 (12.2)	Mid **
Hydrogen Sulphide	H2S-25P		•	N/A	0 - 25 PPM	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Hydrogen Sulphide	H2S-100P		•	N/A	0 - 100 PPM	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Methane	CH4-100L	•		5.0%	0 - 100% LEL	-40 to 122 (-40 to 50)	7500 (696.7)	49 (14.9)	High **
Methanol	CH3OH-100L	•		6.7%	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Nitric Oxide	NO-100P		•	N/A	0 - 100 PPM	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Mid **
Nitrogen Dioxide	NO2-10P		•	N/A	0 - 10 PPM	-4 to 122 (-20 to 50)	7500 (696.7)	49 (14.9)	Low **
Oxygen	O2-25V		•	N/A	0 - 25% by Vol	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Mid **
Ozone	O3-1P		•	N/A	0 - 1 PPM	-4 to 122 (-20 to 50)	5000 (464.5)	40 (12.2)	High **
Iso-Pentane	C5H12-100L	•		1.4%	0 - 100% LEL	-40 to 122 (-40 to 50)	5000 (464.5)	40 (12.2)	Low **
Phosphine	PH3-1P		•	N/A	0 - 1 PPM	-4 to 104 (-20 to 40)	5000 (464.5)	40 (12.2)	Low **
Phosphine	PH3-5P		•	N/A	0 - 5 PPM	-4 to 104 (-20 to 40)	5000 (464.5)	40 (12.2)	Low **
Propane	C3H8-100L	•		2.1%	0 - 100% LEL	-40 to 122 (-40 to 50)	7500 (696.7)	49 (14.9)	Low **
Silane	SiH4-50P		•	N/A	0 - 50 PPM	-4 to 104 (-20 to 40)	5000 (464.5)	40 (12.2)	Mid **
Sulphur Dioxide	SO2-6P		•	N/A	0 - 6 PPM	-4 to 122 (-20 to 50)	5000 (464.5)	40 (12.2)	Low **

**Note\*\*:** Low = 0.5' to 1.5' (0.15 to 0.31m) above floor; Mid = 4.0 to 6.0' (1.20 to 1.83m) above floor; High = 0.5' to 1.5' (0.15 to 0.46m) below ceiling



STANDARD ORDERING			Model # Example: Q6-CO/NO2-10P -OR- 146117
Model #	Item #	Description	
Q6-CO/NO2-10P	146117	Main Unit: CO (0-250 ppm)   Remote Unit: NO2 (0-10 ppm)	
B6-CO/NO2-10P	146119	BACnet™ Main Unit: CO (0-250 ppm)   Remote Unit: NO2 (0-10 ppm)	

CUSTOM ORDERING		Model # Example: Q6-CO/CH4-100L	MODEL #
1. Sensor Series <i>Select One (1)</i>	Q6-CO = Main Unit (CO)   B6-CO = BACnet™ Main Unit (CO)		
2. Gas Span Code	Enter the Gas Span Code from the Sensor Selection and Specification Table on the previous page		

ACCESSORIES ORDERING   Q6, B6			Model # Example: 85930-006-000 -OR- 128901
Model #	Item #	Description	
85930-006-000	128901	Calibration Adaptor Kit for Q5/B5, Q6/B6	
85930-007-000	130812	Sensor Splash Guard Kit for Q5/B5, Q6/B6	
85930-040-000	131510	Duct Mount Kit (Adaptor, Tubing, Pitot Tubes) for Q5/B5, Q6/B6	
GSG-1	141059	Gas Sensor Protective Guard (White)	

ACCESSORIES ORDERING   HORN STROBE			Model # Example: FSIG-SLM500A -OR- 136476
Model #	Item #	Description	
FSIG-SLM500A	136476	Streamline Horn and Strobe (Amber)	
FSIG-SLM500B	142976	Streamline Horn and Strobe (Blue)	
FSIG-SLM500G	143013	Streamline Horn and Strobe (Green)	
FSIG-SLM500R	143132	Streamline Horn and Strobe (Red)	

ACCESSORIES ORDERING   MOUNTING BASE			Model # Example: FSIG-SLMBW-012-024GY -OR- 136477
Model #	Item #	Description	
FSIG-SLMBD-012-024GY	142977	Deep Base for FSIG-SLM500 Series; Gray	
FSIG-SLMBW-012-024GY	136477	Wall Mount Base for FSIG-SLM500 Series; Gray	

Note: See Strobe & Alarm Data Sheet if required

ACCESSORIES ORDERING   PROTECTIVE DOME FOR DEEP MOUNTING BASE			Model # Example: FSIG-SLMDG2 -OR- 143149
Model #	Item #	Description	
FSIG-SLMDG2	143149	Optional Protective Dome for Deep Mounting Base and SLM500x Series Horn and Strobe	