

# PMAX-0103



Straight Tube with Bracket

## ► Specifications

### Device


Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Straight Tube with Bracket










### General

Weight	609.5g (1.34lb)
Dimensions	(W x H x D): 140mm x 134mm x 309mm (5.52" x 5.28" x 12.17")
Material	Aluminum
Color	Warm Gray
Warranty	1 Year(s). For extended warranty offering, see <a href="http://www.acti.com/support/warranty">http://www.acti.com/support/warranty</a>

## ► Related Products

### PTZ - Speed Dome

B915	 <p>3MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics</p>
------	---

B916		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 20x Zoom lens, f4.7-94mm/F1.6-3.5 (HOV:62°-2.8°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B922		5MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
B928		5MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:51.14°-2.17°), DC iris, Auto Focus, H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
B943		3MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:57.6°-2.35°), DC iris, Auto Focus, H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
I910		4MP Outdoor Speed Dome with D/N, Advanced WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:58.78°-2.35°), DC iris, Auto Focus, H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO
I915		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 36x Zoom lens, f4.6-165.6mm/F1.55-5.0 (HOV:62.7°-2.7°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics
I96		2MP Outdoor Speed Dome with D/N, Extreme WDR, ELLS, 30x Zoom lens, f4.3-129mm/F1.6-5.0 (HOV:66.4°-2.61°), DC iris, Auto Focus, H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO
I97		2MP Video Analytics Outdoor Speed Dome with D/N, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP67, IK10, DI/DO, Built-in Analytics
I98		2MP Video Analytics Outdoor Speed Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 33x Zoom lens, f4.5-148.5mm/F1.6-5.0 (HOV:69.3°-3°), DC iris, Auto Focus, H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, High PoE/AC24V, IP66, IK10 (metal casing), DI/DO, Built-in Analytics