

# PMAX-0313



Heavy Duty Wall Mount for Indoor Domes (for B5x, B6x, D6x, E6x, I5x)

## ► Specifications

### Device


Product Type	Camera Mount
Application Environment	Indoor
Description	Heavy Duty Wall Mount for Indoor Domes (for B5x, B6x, D6x, E6x, I5x)

### General

Weight	975.5g (2.15lb)
Dimensions	(W x H x D): 207mm x 160mm x 140mm (8.15" x 6.30" x 5.51")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)


## ► Related Products


### Dome - Dome


E63A		5MP Indoor Dome with D/N, Adaptive IR, Basic WDR, Vari-focal lens, f2.8-12mm/F1.4 (HOV:66.62°-28.88°), H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE, IK09, DI/DO
------	---	--


E67  2MP Indoor Dome with Basic WDR, SLLS, Vari-focal lens

**Dome - Zoom Dome**


B61  5MP Indoor Zoom Dome with D/N, Adaptive IR, Basic WDR, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:85.7°-30.5°), DC iris, Auto Focus, H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IK09, DI/DO


B64  1.3MP Indoor Zoom Dome with D/N, Adaptive IR, Basic WDR, SLLS, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:90.6°-31.8°), DC iris, Auto Focus, H.264, 720p/60fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IK09, DI/DO


B67  3MP Indoor Zoom Dome with D/N, Adaptive IR, Superior WDR, 3x Zoom lens, f3-9mm/F1.2-2.1 (HOV:84.5°-29.8°), DC iris, Auto Focus, H.264, 1080p/30fps, DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IK09, DI/DO


E618  3MP Indoor Zoom Dome with D/N, Adaptive IR, Superior WDR, 4.3x Zoom lens, f3.1-13.3mm/F1.4-4.0 (HOV:64.4°-26.4°), P-Iris, Auto Focus (for installation), H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE, IK09, DI/DO


**Dome - Hemispheric Dome**

B511A  12MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics

B57  6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:187°), H.264, Dewarping, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics

B57A  6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics

I51  5MP Indoor Hemispheric Dome with D/N, Advanced WDR, SLLS, Fixed lens, f1.05mm/F2.8 (HOV:180° (overview area), 109.8° (high detail area)), H.264, Dewarping, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO

Q51  2MP Heat Map Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:171°), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics