100/200/600A MEDIUM SPLIT CORE CURRENT TRANSFORMERS

Split-core current transformers provide linear output voltage that is directly proportional to the input current. These transformers are safely and easily installed over existing electrical power lines without disconnecting the lines or interrupting service.

DENT's energy monitoring components are used for a variety of applications including building automation, tenant submetering, performance verification, energy management, and new technology assessment.

KEY SPECIFICATIONS					
Window Size	1.25" (3.20 cm)				
Current Range	100A Model: 5 - 130A AC 200A Model: 4 - 260A AC 600A Model: 12 - 780A AC				
Output	333 mV at rated current				
Ratio Error*	<1% at rated current (typical)				
Phase Error*	<2° at rated current (typical)				

ELECTRICAL

Output 333 mV at rated current

Wire Polarity White = Hi, positive (+)
Black = Low, negative (-)

Frequency Range 50 to 400 Hz

MECHANICAL

Case Material Epoxy encapsulated housing

Leads 3 M (9.8'), twisted pair, 20

AWG

Operating Temperature -20° to 55°C (-4° to 131°F)

SAFETY

Working Voltage 600 VAC, Category III

Dielectric Strength 5000 VAC around case 600V rated leads

Certification Conforms to:

Intertek

Conforms to: UL STD 61010-1 EN 60044-1 Certified to: CAN/CSA STD C22.2 No. 61010-1

CONTACT US

DENT Instruments, Inc. Energy & Power Measurement Solutions An ISO 9001:2008 Certified Company

541.388.4774 | 800.388.0770 www.DENTINSTRUMENTS.COM

925 SW EMKAY DRIVE

BEND, OREGON 97702 USA


INSTRUMENTS







DENT	NOMINAL	USEFUL CURRENT RANGE (Amps)	DIMENSIONS				
DENT P/N	RATING (Amps)		A	В	C	D	E
CT-SCM-0100 CT-SCM-0200 CT-SCM-0600	100 200 600	5 - 130A AC 4 - 260A AC 12—780A AC	8.26 cm (3.25")	8.51 cm (3.35")	2.54 cm (1.00")	3.18 cm (1.25")	3.18 cm (1.25")



PART NUMBERS

CT-SCM-0100-U 100A Medium Split Core
CT-SCM-0200-U 200A Medium Split Core
CT-SCM-0600-U 600A Medium Split Core