

| ANIXTER PART NO. | CBL-STAT50                                            |
|------------------|-------------------------------------------------------|
| Description      | 24 AWG 4-pair plenum Category 3 data cable Plen-Lan 3 |
| Rating           | UL Standard 444, ICEA S-80-576, EIA/TIA-568, CSA FT6  |
| Certifications   | ETL and UL Verified Category 3                        |

## CONSTRUCTION PARAMETERS

|            | Information                                                  | Diameter (in.) |
|------------|--------------------------------------------------------------|----------------|
| Conductors | Solid bare copper                                            | 0.020          |
| Insulation | Low smoke PVC                                                | 0.035          |
| Pair Lays  | Each pair has different lay length for crosstalk prevention. |                |
| Rip cord   | Polyester                                                    |                |
| Jacket     | Low smoke PVC                                                | 0.160          |

## ELECTRICAL AND ENVIRONMENTAL PROPERTIES

|                    |                   |
|--------------------|-------------------|
| Temperature Rating | 75 °C             |
| Operating Voltage  | 300 V rms maximum |

## APPEARANCE AND PACKAGING

|              |                                                                                                                        |
|--------------|------------------------------------------------------------------------------------------------------------------------|
| Pair Colors  | White/blue with blue/white, white/orange with orange/white, white/green with green/white, white/brown with brown/white |
| Jacket Color | Natural                                                                                                                |
| Cable Length | 50 feet with RJ45 jacks. Straight wiring.                                                                              |

