

## Introduction

The Johnson Controls® Low Differential Pressure Transducer DP140 Series offers an excellent price-to-performance ratio and meets the requirements in all typical HVAC applications. The DP140 is a low differential pressure transducer that uses a dead-ended capacitive sensing element and requires minimal amplification. The DP140 delivers  $\pm 1\%$  full-scale (FS) accuracy with  $\pm 0.25\%$  and  $\pm 0.5\%$  accuracy options with pressure ranges from 0.1 in. W.C. up to  $\pm 25$  in. W.C. The DP140 has a small footprint and an AC power option.

**Figure 1: DP140 Series Transducer**



## Applications

Use the Low Differential Pressure Transducer DP140 Series in the following applications:

- HVAC systems
- Air flow stations
- Variable Air Volume (VAV) or fan control
- Filter status
- Static duct and cleanroom pressures

## Features and benefits

The Low Differential Pressure Transducer DP140 delivers excellent accuracy and longterm stability. Features include:

- Excellent price-to-performance ratio
- Reduced installation costs
- $\pm 0.25\%$ ,  $\pm 0.5\%$ ,  $\pm 1\%$  FS accuracy options
- 24 VDC or 24 VAC excitation
- Voltage or milli-amp analog outputs
- Reverse wiring protection

- Internal regulation
- Fire retardant case, UL 94 V-0 approved
- CE and RoHS compliant

## High performance

The DP140 is a high-value solution with exceptional features, quality, and performance.

## Cost-saving installation

The design of the DP140 reduces installation costs and increases overall operating efficiency. Installation is easy with integral mounting tabs, pressure connections located on the face of the unit, and a screw terminal strip for electrical termination.


## IP67-rated housing

The DP140 housing is a robust IP67-rated design, sealed with a gasket to make it wash-down capable for difficult applications. The DP140 includes a conduit fitting for easy installation and wiring.

## Dimensions

The dimensions of the DP140 Transducer are shown in the following figures.

**Figure 2: Dimensions of the DP140 Transducer, in. (mm)**



## Ordering information

See the following table for ordering options for the DP140 Low Differential Pressure Transducers. All units have a 1/2 in. conduit electrical fitting. For example, DP140X25B21F is model DP140,  $\pm 0.25$  in. W.C., bidirectional range, 4 mA to 20 mA, 1/2 in. conduit fitting,  $\pm 0.25\%$  accuracy.

**Table 1: Product codes**

Product code	Range, in in. W.C.	Direction	Output	Accuracy
DP140005U21C	0 to 5	Unidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP1402X5U21C	0 to 2.5	Unidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP1402X5U11C	0 to 2.5	Unidirectional	0 VDC to 5 VDC	$\pm 1\%$ FS
DP140X25B21C	$\pm 0.25$	Bidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP140005U21D	0 to 5	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP1402X5U21D	0 to 2.5	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP140005U11C	0 to 5	Unidirectional	0 VDC to 5 VDC	$\pm 1\%$ FS
DP140005U21F	0 to 5	Unidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP140025U21D	0 to 25	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP140010U21C	0 to 10	Unidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP1400X1B11F	$\pm 0.1$	Bidirectional	0 VDC to 5 VDC	$\pm 0.25\%$ FS
DP140010U21D	0 to 10	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP1402X5U21F	0 to 2.5	Unidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP140X25B21F	$\pm 0.25$	Bidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP140X25B11C	$\pm 0.25$	Bidirectional	0 VDC to 5 VDC	$\pm 1\%$ FS
DP140001U21F	0 to 1	Unidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP140X25U21C	0 to 0.25	Unidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP140010U11D	0 to 10	Unidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP140001U11F	0 to 1	Unidirectional	0 VDC to 5 VDC	$\pm 0.25\%$ FS
DP140001U21C	0 to 1	Unidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP140X25B11F	$\pm 0.25$	Bidirectional	0 VDC to 5 VDC	$\pm 0.25\%$ FS
DP140X25U21D	0 to 0.25	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP140001U21D	0 to 1	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP1400X5U21C	0 to 0.5	Unidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP140025U11D	0 to 25	Unidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP1400X5B21C	$\pm 0.5$	Bidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP1400X5B21D	$\pm 0.5$	Bidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP1400X1B21F	$\pm 0.1$	Bidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP140001U11D	0 to 1	Unidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP140010U21F	0 to 10	Unidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP1400X5B21F	$\pm 0.5$	Bidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP1402X5B21C	$\pm 2.5$	Bidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP140005B21C	$\pm 5$	Bidirectional	4 mA to 20 mA	$\pm 1\%$ FS
DP140050U21D	0 to 50	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP140X25B11D	$\pm 0.25$	Bidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP140010U11C	0 to 10	Unidirectional	0 VDC to 5 VDC	$\pm 1\%$ FS
DP1400X5U21D	0 to 0.5	Unidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP140005U11D	0 to 5	Unidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP1400X1B11D	$\pm 0.1$	Bidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP140025U21F	0 to 25	Unidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP1402X5U11F	0 to 2.5	Unidirectional	0 VDC to 5 VDC	$\pm 0.25\%$ FS
DP140X25U21F	0 to 0.25	Unidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP1400X1B21D	$\pm 0.1$	Bidirectional	4 mA to 20 mA	$\pm 0.5\%$ FS
DP140001U11C	0 to 1	Unidirectional	0 VDC to 5 VDC	$\pm 1\%$ FS
DP1400X5B11D	$\pm 0.5$	Bidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP1400X1B11C	$\pm 0.1$	Bidirectional	0 VDC to 5 VDC	$\pm 1\%$ FS
DP140X25U11D	0 to 0.25	Unidirectional	0 VDC to 5 VDC	$\pm 0.5\%$ FS
DP1400X5U21F	0 to 0.5	Unidirectional	4 mA to 20 mA	$\pm 0.25\%$ FS
DP140X25U11C	0 to 0.25	Unidirectional	0 VDC to 5 VDC	$\pm 1\%$ FS

**Table 1: Product codes**

Product code	Range, in in. W.C.	Direction	Output	Accuracy
DP1400X5U11D	0 to 0.5	Unidirectional	0 VDC to 5 VDC	±0.5% FS
DP1402X5B21F	±2.5	Bidirectional	4 mA to 20 mA	±0.25% FS
DP1400X5B11F	±0.5	Bidirectional	0 VDC to 5 VDC	±0.25% FS
DP1402X5B21D	±2.5	Bidirectional	4 mA to 20 mA	±0.5% FS
DP1400X5U11C	0 to 0.5	Unidirectional	0 VDC to 5 VDC	±1% FS
DP140005U11F	0 to 5	Unidirectional	0 VDC to 5 VDC	±0.25% FS
DP140001B21F	±1	Bidirectional	4 mA to 20 mA	±0.25% FS
DP1402X5U11D	0 to 2.5	Unidirectional	0 VDC to 5 VDC	±0.5% FS
DP140001B21D	±1	Bidirectional	4 mA to 20 mA	±0.5% FS
DP140010U11F	0 to 10	Unidirectional	0 VDC to 5 VDC	±0.25% FS
DP1400X5B11C	±0.5	Bidirectional	0 VDC to 5 VDC	±1% FS
DP1400X1U21C	0 to 0.1	Unidirectional	4 mA to 20 mA	±1% FS
DP140001B11D	±1	Bidirectional	0 VDC to 5 VDC	±0.5% FS
DP140X25B21D	±0.25	Bidirectional	4 mA to 20 mA	±0.5% FS
DP140001B21C	±1	Bidirectional	4 mA to 20 mA	±1% FS
DP1400X1U21D	0 to 0.1	Unidirectional	4 mA to 20 mA	±0.5% FS
DP140005B21D	±5	Bidirectional	4 mA to 20 mA	±0.5% FS
DP140005B21F	±5	Bidirectional	4 mA to 20 mA	±0.25% FS
DP140100U11D	0 to 100	Unidirectional	0 VDC to 5 VDC	±0.5% FS
DP140050U11C	0 to 50	Unidirectional	0 VDC to 5 VDC	±1% FS
DP1400X1U11D	0 to 0.1	Unidirectional	0 VDC to 5 VDC	±0.5% FS
DP140001B11C	±1	Bidirectional	0 VDC to 5 VDC	±1% FS
DP1402X5B11F	±2.5	Bidirectional	0 VDC to 5 VDC	±0.25% FS
DP140025U11F	0 to 25	Unidirectional	0 VDC to 5 VDC	±0.25% FS
DP1400X1U21F	0 to 0.1	Unidirectional	4 mA to 20 mA	±0.25% FS
DP1400X1U11C	0 to 0.1	Unidirectional	0 VDC to 5 VDC	±1% FS
DP1400X5U11F	0 to 0.5	Unidirectional	0 VDC to 5 VDC	±0.25% FS
DP140005B11D	±5	Bidirectional	0 VDC to 5 VDC	±0.5% FS
DP140005B11C	±5	Bidirectional	0 VDC to 5 VDC	±1% FS
DP140050U11D	0 to 50	Unidirectional	0 VDC to 5 VDC	±0.5% FS
DP1402X5B11D	±2.5	Bidirectional	0 VDC to 5 VDC	±0.5% FS
DP140X25U11F	0 to 0.25	Unidirectional	0 VDC to 5 VDC	±0.25% FS
DP140001B11F	±1	Bidirectional	0 VDC to 5 VDC	±0.25% FS
DP1400X1U11F	0 to 0.1	Unidirectional	0 VDC to 5 VDC	±0.25% FS
DP140005B11F	±5	Bidirectional	0 VDC to 5 VDC	±0.25% FS
DP140025U21C	0 to 25	Unidirectional	4 mA to 20 mA	±1% FS
DP140050U11F	0 to 50	Unidirectional	0 VDC to 5 VDC	±0.25% FS
DP140025U11C	0 to 25	Unidirectional	0 VDC to 5 VDC	±1% FS
DP140005U31C	0 to 5	Unidirectional	0 VDC to 10 VDC	±1% FS
DP140001U31C	0 to 1	Unidirectional	0 VDC to 10 VDC	±1% FS
DP1402X5U31C	0 to 2.5	Unidirectional	0 VDC to 10 VDC	±1% FS
DP1400X5U31C	0 to 0.5	Unidirectional	0 VDC to 10 VDC	±1% FS
DP140X25U31C	0 to 0.25	Unidirectional	0 VDC to 10 VDC	±1% FS
DP140010U31C	0 to 10	Unidirectional	0 VDC to 10 VDC	±1% FS
DP140X25B31C	±0.25	Bidirectional	0 VDC to 10 VDC	±1% FS
DP1400X5B31C	±0.5	Bidirectional	0 VDC to 10 VDC	±1% FS
DP1400X1B31C	±0.1	Bidirectional	0 VDC to 10 VDC	±1% FS
DP140005B31C	±5	Bidirectional	0 VDC to 10 VDC	±1% FS
DP140001B31C	±1	Bidirectional	0 VDC to 10 VDC	±1% FS
DP1402X5B31C	±2.5	Bidirectional	0 VDC to 10 VDC	±1% FS

## Technical specifications

Table 2: Differential Pressure Transducer DP110 technical specifications

Description		Specification
<b>Performance data</b>	Accuracy RSS1, at constant temperature	±1.0% FS, standard ±0.5% FS, ±0.25% FS, optional
	Non-linearity, BFSL	±0.98% FS, standard ±0.38% FS, ±0.22% FS, optional
	Hysteresis	0.10% FS
	Non-repeatability	0.05% FS
<b>Thermal effects</b>  ① <b>Note:</b> Units calibrated at nominal 70° F. Maximum thermal error calculated from this data.	Compensated range	0°F to 150°F (-18°C to 65°C)
	Zero shift % FS at 100°F (% FS at 50°C)	±0.033 (±0.06)
	Span shift % FS at 100°F (% FS at 50°C)	±0.033 (±0.06)
	Maximum line pressure	10 psi, 277 in. W.C.
	Overpressure	Up to 10 psi (277 in. W.C.) range dependent
	Long term stability	0.5% FS per year
	Warm-up shift	0.1% FS total
<b>Environmental data</b>	Operating temperature  ① <b>Note:</b> Operating temperature limits of the electronics only. Pressure media temperatures may be considerably higher.	0°F to 150°F (-18°C to 65°C)
	Storage temperature	-40°F to 185°F (-40°C to 85°C)
<b>Pressure media</b>	Clean air or similar nonconducting gases	
<b>Physical specifications</b>	Pressure fittings	1/4 in. push-on tube fitting
	Case	Fire retardant glass-filled polyester, UL 94-V approved
	Weight	3 oz
	Electrical connections	Removable terminal block
<b>Position effect</b>	<b>Range</b>	<b>Zero offset (%FS/G)</b>
	0 to 0.5 in. W.C.	0.60
	0 to 1.0 in. W.C.	0.50
	0 to 2.5 in. W.C.	0.22
	0 to 5.0 in. W.C.	0.14
<b>Electrical data, voltage</b>	Circuit	3-wire: Exc, Out, Com
	Excitation or output	9 VDC to 30 VDC or 0 VDC to 5 VDC
	① <b>Note:</b> Calibrated into a 50 K ohm load, operable into a 5 K ohm load or greater	9 VAC to 30 VAC or 0 VDC to 5 VDC
		12 VAC to 30 VAC or 0 VDC to 10 VDC
	Output impedance	<100 ohm
Bidirectional output at zero pressure	2.5 V in case of 0 V to 5 V output 5 V in case of 0 V to 10 V output	

**Table 2: Differential Pressure Transducer DP110 technical specifications**

Description		Specification
<b>Electrical data, current</b>	Circuit	2-wire
	Output ⓘ <b>Note:</b> Calibrated at factory with a 24 VDC loop supply voltage and a 250 ohm load.	4 mA to 20 mA ⓘ <b>Note:</b> Zero and Span FS output factory set to within ±0.16 mA, ±0.08 mA for optional accuracies.
	External load	0 ohm to 800 ohm
	Minimum supply voltage, VDC	$9 + 0.02 \times (\text{resistance of receiver plus line})$
	Maximum supply voltage, VDC	$30 + 0.004 \times (\text{resistance of receiver plus line})$
	Bidirectional output at zero pressure	12 mA
	<b>Compliance</b>	CE Mark - Johnson Controls declares that this product is in Compliance with the essential requirements and other relevant provisions of the EMC and RoHS Directives.
<b>CE</b>		

The performance specifications are nominal and conform to acceptable industry standards. For application at conditions beyond these specifications, consult the local Johnson Controls office. Johnson Controls shall not be liable for damages resulting from misapplication or misuse of its products.

## Product warranty

This product is covered by a limited warranty, details of which can be found at [www.johnsoncontrols.com/buildingswarranty](http://www.johnsoncontrols.com/buildingswarranty).

## Software terms

**Use of the software that is in (or constitutes) this product, or access to the cloud, or hosted services applicable to this product, if any, is subject to applicable end-user license, open-source software information, and other terms set forth at [www.johnsoncontrols.com/techterms](http://www.johnsoncontrols.com/techterms).** Your use of this product constitutes an agreement to such terms.

## Patents

Patents: <https://jciapat.com>

## Single point of contact

APAC	Europe	NA/SA
JOHNSON CONTROLS C/O CONTROLS PRODUCT MANAGEMENT NO. 32 CHANGJIJANG RD NEW DISTRICT WUXI JIANGSU PROVINCE 214028 CHINA	JOHNSON CONTROLS WESTENDHOF 3 45143 ESSEN GERMANY	JOHNSON CONTROLS 507 E MICHIGAN ST MILWAUKEE WI 53202 USA

## Contact information

Contact your local branch office: [www.johnsoncontrols.com/locations](http://www.johnsoncontrols.com/locations)

Contact Johnson Controls: [www.johnsoncontrols.com/contact-us](http://www.johnsoncontrols.com/contact-us)