Rotary Actuator Accessories Catalog Page

Direct Mount Actuator Accessories (Part 1 of 4)

	Code Number	Description	Qty	Non-Spring Return				Spring Return			
	Number			M(VA)9104(6)-AGx- 2Nxx	M9102(4)-xGA-xS	M9106(9)-xGx-2	M(VA)9308/9310	M(VA)9316/9320/9335	M(VA)9203	M(VA)9208	M9220
s	CBL-2000-1	20 in. wire harness, actuator/transmitter to controller	1	•							
orie	CBL-2000-2	20 in. cable, actuator/transmitter to controller, plenum rated	1	•							
VAV esso	CBL-2000-3	72 in. cable, actuator/transmitter To controller, plenum rated	1	-							
VAV Accessories	DPT-2015-0	Differential pressure transmitter, 0 to 1-1/2 in. W.C. (0 to 374 Pa.)	1	•							
	M9000-606	Position indicators	5						-	-	
	M9000-611	Position indicators	5								
	M9000-154	Jackshaft coupler kit, M9108 (16) (24) (32) Series (Ø 1 in.)	1								
rs	M9203-601	Standard coupler kit, M9203 Series (Ø 1/4 to 1/2 in.) (□ 1/4 to 5/16 in.)	1						-		
ato	M9203-602	Retainer for M9203 coupler	5						•		
lndic	M9208-601	Standard coupler kit, M9208 Series (Ø 5/16 to 5/8 in.) (□ 1/4 to 1/2 in.)	1							•	
ositior	M9208-600	Large coupler kit, M9208 Series (Ø 1/2 to 3/4 in.) (□ 3/8 to 9/16 in.)	1							•	
Shaft Couplers / Position Indicators	M9220-601	Standard coupler kit M9220 Series (1/2 to 3/4 in.) (□ 3/8 to 1/2 in.)	1								•
ouple	M9220-600	Jackshaft coupler kit, M9220 Series (3/4 to 1-1/16 in.) (□ 5/8 to 3/4 in.)	1								•
L L L	M9220-610	10 mm square shaft adapter with retainer	1								
Shat	M9220-612	12 mm square shaft adapter with retainer	1								
0	M9220-614	14 mm square shaft adapter with retainer	1								
	M9208-602	Retainer for M9208 coupler	5	1							
	M9220-602	Retainer for M9220 coupler	5								
	M9310-600	Damper Shaft Adaptor for VA9300 actuators	1								
	M9000-152	Reinforcement plate for mounting to thin sheet metal	1								
	M9000-158	Tandem mounting bracket	1								
	M9000-160	Anti-rotation bracket	1								
ng its	M9000-604	Anti-rotation bracket	1						-	-	
Mounting Brackets	M9300-100D	Butterfly Valve Mounting Kit for Tandem M9300 Series Non-Spring Return Electric Actuators to 4, 5 and 6 in. (DN 100, 125 & 150)	1					•			
2	M9300-100S	Butterfly Valve Mounting Kit for a Single M9300 Series Non-Spring Return Electric Actuator to 2, 3 and 4 in. (DN 50, 80 & 100)	1					•			
	M9300-200S	Butterfly Valve Mounting Kit for a Single M9300 Series Non-Spring Return Electric Actuator to 8 in. (DN 200)	1					•			

Direct Mount Actuator Accessories (Part 2 of 4)

	Code	Description	Qty	Non	-Spr	ing F	Retu	rn	Spri	ng Re	turn
	Number			M(VA)9104(6)-AGx- 2Nxx	M9102(4)-xGA-xS	M9106(9)-xGx-2	M(VA)9308/9310	M(VA)9316/9320/9335	M(VA)9203	M(VA)9208	M9220
	DMPR-KC003	Blade pin extension (Ø 1/2 x 7 in.) for D1300 dampers Not used with VA9308, VA9320, VA9335	1			•	•	•	-	•	•
	DMPR-KC054	Damper blade arm for D1300 dampers	1								
	DMPR-KC100	Damper blade linkage for D1300 dampers	1								
	DMPR-KC102	Damper push rod, Ø 5/16 x 48 in. length	1								
	DMPR-KC254	Damper mount linkage kit for D1300 dampers	1								
	DMPR-KC260	Damper mount linkage kit for D1300 dampers	1								
	DMPR-KC300	Ball joint for Ø 5/16 in. rod, 1/4-20 x 9/16 in. thread mount	10			-					
	M9000-150	Damper mount linkage kit for D1300 dampers	1								
	M9000-151	Remote mounting kit with crankarm and damper linkage	1					-			
ŝ	M9000-153	Crankarm kit	1								
orie	M9000-170	Remote mounting kit (horizontal) with crankarm	1								
SSS	M9000-171	Remote mounting kit (vertical) with crankarm	1								-
/ Acce	M9000-270	Remote mounting kit (horizontal) with crankarm and damper linkage for D1300 dampers	1								•
Damper Linkages / Accessories	M9000-271	Remote mounting kit (vertical) with crankarm and damper linkage for D1300 dampers	1								•
ink	M9000-400	Jackshaft mounting kit, Ø 1/2 to 1.05 in.	1				-	-			-
er L	M9000-402	Replacement hardware for M9000-400 jackshaft mounting kit	1							•	-
du	M9000-605	Ball joint for Ø 1/4 or 5/16 in. rods, 5/16-24 x 33/64 in. thread mount	5						-	•	-
Da	M9203-100	Remote mounting kit with crankarm	1						-		
	M9203-110	Universal mounting kit	1						-		
	M9203-115	Universal mounting kit with crankarm	1						-		
	M9203-150	Crankarm kit	1						-		
	M9203-250	Remote mounting kit with crankarm and damper linkage for D1300 dampers	1						-		
	M9208-100	Remote mounting kit with crankarm	1							•	
	M9208-150	Crankarm kit	1							•	
	M9208-250	Remote mounting kit with crankarm and damper linkage for D1300 dampers	1							•	
	M9220-605	Ball joint for M8x1.25 threaded rod, M8x1.25 x 16.5 mm thread mount	5								•

Direct Mount Actuator Accessories (Part 3 of 4)

Direct	Code Number	ator Accessories (Part 3 of 4) Description	Qty	Non-Spring Return				Spring Return			
	Number			M(VA)9104(6)-AGx- 2Nxx	M9102(4)-xGA-xS	M9106(9)-xGx-2	M(VA)9308/9310	M(VA)9316/9320/9335	M(VA)9203	M(VA)9208	M9220
	M9000-155	Manual handle	1								
	M9000-518	Ball valve linkage for non-spring return, 2-1/2 to 6 in. VG1000 flanged valves with 11 mm square stem	1								
	M9000-519	Ball valve linkage for spring return, 2-1/2 to 6 in. VG1000 flanged valves with 11 mm square stem	1								-
	M9000-530	Linkage for 2-1/2 in. flanged iron globe valves for single actuator mounting	1					■ ¹			•
	M9000-531	Linkage for 3 in. flanged iron globe valves for single actuator mounting	1					■ ¹			
		Linkage for 4 in. flanged iron globe valves for single actuator mounting	1					■ ¹			-
	M9000-532	Linkage for 3 in. flanged iron globe valves for tandem actuator mounting	1					■ ¹			•
		Linkage for 4 in. flanged iron globe valves for tandem actuator mounting	1					■ ¹			•
kage	M9000-533	Linkage for 5 in. flanged iron globe valves for single actuator mounting	1					■ ¹			•
Valve Linkages	M9000-534	Linkage for 5 in. flanged iron globe valves for tandem actuator mounting	1					• ¹			-
Val	M9000-535	Linkage for 6 in. flanged iron globe valves for single actuator mounting	1					• ¹			-
	M9000-536	Linkage for 6 in. flanged iron globe valves for tandem actuator mounting	1					1			-
	M9000-537	Linkage for 4 in. flanged iron globe valves for tandem actuator mounting	1					1			-
	M9000-539	Adapter for M9000-53x linkages									
	M9000-551	Ball valve linkage, 1/2 to 1 in. hot/chilled water applications	1								
	M9000-560	Ball valve linkage, 1/2 to 2 in. hot/chilled water applications	1						•	•	
	M9000-561 M9000-607	Thermal barrier Position indicators, VA9203 and VA9208 Series	1 5				•				
	M9000-610	Tandem actuators, VA9203 and VA9208 Series Tandem actuator adapter kit for VG2000 Series iron globe valve linkages	1								•
	M9310-500	Ball valve linkage kit for M9310 on VG1000 Series valves	1								
	M9000-700	Universal Ball Valve Linkage Kit	1								
	M9000-310	Weather shield NEMA 3R, control dampers and VG2000 Series iron globe valve linkages, non-spring return	1			•					
	M9000-320	Weather shield NEMA 3R, control dampers and VG2000 Series iron globe valve linkages, spring return	1								•
ş	M9000-322	Weather shield, NEMA 4X (IP66), control dampers	1	-					-	•	
nielc	M9000-323	Weather shield, NEMA 4X (IP66), control dampers	1	l				•			
Weather Shields	M9000-330	Weather shield NEMA 3R, VG1000 Series ball valves with M9000-518 linkage, non-spring return	1								
Weat	M9000-340	Weather shield NEMA 3R, VG1000 Series ball valves with M9000-517 or M9000-519 linkage, spring return	1								
	M9000-342	Weather shield, NEMA 4X (IP66), 1/2 to 2 in. VG1000 Series ball valves	1	•	-		•		-	-	
	M9000-343	Weather shield, NEMA 4X (IP66), 2-1/2" to 6 in. VG1000 Series ball valves	1					•			

1. Adapter kit M9000-539 is required.

Direct Mount Actuator Accessories (Part 4 of 4)

	Code Number	Description	Qty	Non-Spring Return				Spring Return			
				M(VA)9104(6)-AGx- 2Nxx	M9102(4)-xGA-xS	M9106(9)-xGx-2	M(VA)9308/9310	M(VA)9316/9320/9335	M(VA)9203	M(VA)9208	M9220
it	M9300-2	Auxiliary Switch Kit 2x SPDT									
Switch Kit			1				•	•			
t.	M9300-1K	Potentiometer Feedback Kit 1k Ohm	1					•			
Ϋ́	M9300-2K	Potentiometer Feedback Kit 2k Ohm	1								
act	M9300-10K	Potentiometer Feedback Kit 10k Ohm	1					•			
Feedback Kit	M9300-140	Potentiometer Feedback Kit 140 Ohm	1				•	•			
sd	M9203-603	Adjustable stop kit	1						-		
Stol	M9208-603	Adjustable stop kit	1							•	
Adj. Stops	M9220-603	Adjustable stop kit	1								•
s	M9000-105	Pluggable 3-terminal block	1			-					
1g orie	M9000-106	Pluggable 4-terminal block	1								
Wiring Accessories	M9104-100	Conduit adapter for 3/8 in. flexible metal conduit	10								
≤ 00	M9200-100	Threaded conduit adapters for 1/2 in. electrician's fittings	5								•
	M9300-100	Threaded conduit adapters for 1/2 in. electrician's fittings	5				-				
Tools	M9220-604	Manual crank, long, crank radius 2-13/16 in. (75 mm)	5							•	•
To	M9208-605	Manual crank, short, crank radius 1-13/16 in. (46.5 mm)	5							•	
	M9000-103	Transformer, 14 VA Class 2, 120 to 24 VAC 60 Hz	1								
	M9000-104	Transformer, 14 VA Class 2, 230 to 24 VAC 60 Hz	1								
	Y63T22-0	Transformer, 50 VA Class 2, 120/208/240 to 24 VAC 60 Hz, box mounting	1	•		•	-		-	•	•
	Y63T31-0	Transformer, 50 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot/box mounting	1	•	-	•	-		-	-	•
	Y64T15-0	Transformer, 92 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot mounting	1	•		•	-		-	-	•
snoe	Y64T21-0	Transformer, 92 VA Class 2, 120/208/240 to 24 VAC 60 Hz, box mounting	1	•	-	•	-		-	•	•
Miscellaneous	Y64T22-0	Transformer, 92 VA Class 2, 120/208/240 to 24 VAC 60 Hz, box mounting	1	•	-	•	-		-	•	•
lisc	Y65A13-0	Transformer, 40 VA Class 2, 120 to 24 VAC 60 Hz, foot mounting	1	•		•				-	
2	Y65A21-0	Transformer, 40 VA Class 2, 120 to 24 VAC 60 Hz, box mounting	1	•		•				-	
	Y65G13-0	Transformer, 40 VA Class 2, 24 to 24 VAC 60 Hz isolation, foot mounting	1	•	-	•	-		•	•	•
	Y65S13-0	Transformer, 40 VA Class 2, 208/240 to 24 VAC 60 Hz, foot mounting	1	•	-	•	-		•	•	•
	Y66T12-0	Transformer, 75 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot mounting	1	•		•	-		-	-	-
	Y66T13-0	Transformer, 75 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot mounting	1	•	-	•	-		-	•	•



Rotary Actuator Accessories Catalog Page (Continued) M9104-AGx-2Nxx and M9106-AGx-2Nxx Series Actuator Accessories



M9106-AGS-2N

M9104-AGx-2Nxx and M9106-AGx-2Nxx Series Actuator Accessories

M9106-AGA-2N

	Code Number	Description	Qty
Variable Air Volume (VAV) System Acces	sories		
	CBL-2000-1	20 in. (0.5 m) plenum rated wiring harness	1
(CBL-2000-1.11)	CBL-2000-2	20 in. (0.5 m) plenum rated wiring harness	1
(CBL-2000-34)	CBL-2000-3	72 in. (1.8 m) plenum rated wiring harness	1
(DPT-2015-0.til)	DPT-2015-0	0 to 1.5 in W.C. (0 to 375 Pa) differential pressure transmitter	1

Rotary Actuator Accessories Catalog Page (Continued) M9102-xGA-xS and M(VA)9104-xGA-xS Series Actuator Accessories



M9102/9104-xGA-2S (M9102-AGA-2S.til)



M9102/9104-xGA-3S (M9102-IGA-3S.tif)

M9102-xGA-xS and M(VA)9104-xGA-xS Series Actuator Accessories

	Code Number	Description	Qty
Valve Linkages			
(M9000-550 I/0 I.cdr) (M9000-550 I/0 I.cdr) (M9000-550 I/0 I.cdr)	M9000-551	VG1000 ball valve linkage (for use with M9104 Series actuators only)	1
	M9000-561	Thermal barrier for M9000-560 and M9000-551 ball valve linkages. Permits use of M(VA)9xxx actuators on VG1000 Series ball valves with low-pressure steam	1
(M9000_561.jpg)	M9000-700	Universal Ball Valve Linkage Kit	
Veather Shields			
	M9000-342	Weather shield NEMA4x (IP66), 1/2 to 2 in. for VG1000 Series ball	1
(M9000_341.jpg)		valves	
Wiring Accessories			
(M9104-100.67)	M9104-100	3/8 in. (10 mm) flexible metal conduit adapter kit (for use with M9102-xxx-2S or M9104-xxx-2S actuators with integrated wiring harness only)	10

M9106-xGx-2 and M9109-xGx-2 Series Actuator Accessories



M9106-GGA-2 (M9106-GGA-2.til)

M9106-xGx-2 and M9109-xGx-2 Series Actuator Accessories

	Code Number	Description ¹	Qty
Mounting Brackets			1
(M900-160.6/)	M9000-160	Anti-rotation bracket for M9106(9) and M9108(16)(24)(32) Series actuators	1
Damper Linkages / Accessories			1
(DMPR-KC003.III)	DMPR-KC003	Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)	1
Weather Shields			1
(M9000-310.#)	M9000-310	NEMA 3R weather shield for control dampers	1
Wiring Accessories			
(M9000-105.8/)	M9000-105	Pluggable 3-terminal block	1
(M9000-106. il)	M9000-106	Pluggable 4-terminal block	1

1. Ø means round shaft size (diameter); □ means square shaft size (each side)

M9108, M9116, M9124, and M9132 Series Actuator Accessories



M9108-AGA-2 (M9108-AGA-2.til)

M9108, M9116, M9124, and M9132 Series Actuator Accessories (Part 1 of 4)

M9108, M9116, M9124, and M9132 Series	Code Number	Description ¹	Qty
Shaft Couplers / Position Indicators			
(M9000-154.0) (from LIT-1900167)	M9000-154	Jackshaft coupler kit for M9108 (16) (24) (32) Series actuators, (Ø 1 in.)	1
Mounting Brackets			
(M9000-152.iff)	M9000-152	Reinforcing plate for mounting to thin sheet metal	1
(M9000-158.81)	M9000-158	Tandem mounting bracket	1
(M9000-160.87)	M9000-160	Anti-rotation bracket	1
Damper Linkages / Accessories			
(DMPR-KC003.81)	DMPR-KC003	Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)	1
(DMPR-KC054.iii)	DMPR-KC054	Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)	1

M9108, M9116, M9124, and M9132 Series Actuator Accessories (Part 2 of 4)

	Code Number	Description ¹	Qty
(DMPR-KC100.01)	DMPR-KC100	Damper blade linkage (for use with D1300 dampers only)	1
	DMPR-KC102	Damper push rod, Ø 5/16 x 48 in.	1
DMPR-KC102.81)	DMPR-KC254	Damper mount linkage kit (for use with D1300 dampers only)	1
DMPR-KC260.ef)	DMPR-KC300	Ball joint for Ø 5/16 in. rod, 1/4-20 x 9/16 in. thread mount	10
M9000-150.8()	M9000-150	Damper mounting kit for remote, inside-duct mounting an M9108 (16) (24) Series actuator to a three-blade or larger damper	1
International (Medicine 151.48)	M9000-151	Remote mounting kit, with crankarm and damper linkage for M9108 (16) (24) Series actuators Use the M9000-151 linkage only on three-blade or larger dampers (not for use with M9132 Series actuators or tandem applications)	1
M9000-153.0/)	M9000-153	Crankarm kit (not for use with M9132 Series actuators or tandem applications)	1
	M9000-400	Jackshaft mounting kit, Ø 0.5 to 1.05 in.	1
(M9000_400.jpg)	M9000-402	Replacement hardware for M9000-400 jackshaft mounting kit	1

M9108, M9116, M9124, and M9132 Series Actuator Accessories (Part 3 of 4)

M9106, M9116, M9124, and M9132 Se	Code Number	Description ¹	Qty
Valve Linkages			
	M9000-155	Manual handle	1
(M9000-155.iif)			
1	M9000-530	VG2000 linkage kit for single M9116 (24) Series electric actuator and Johnson Controls® 2-1/2 in. cast iron globe valves with 3/8 in. stems	1
	M9000-531	VG2000 linkage kit for a single M9116 (24) Series electric actuator and Johnson Controls 3 to 4 in. cast iron globe valves with 3/8 in. stems	1
	M9000-533	VG2000 linkage kit for a single M9124 Series electric actuator and Johnson Controls 5 in. cast iron globe valves with 1/2 in. stems	1
1	M9000-535	VG2000 linkage kit for a single M9124 Series electric actuator and Johnson Controls 6 in. cast iron globe valves with 1/2 in. stems	1
(M9000-531.tif)			
	M9000-532	VG2000 linkage kit for tandem M9124 Series electric actuators and Johnson Controls 3 to 4 in. cast iron globe valves with 3/8 in. stems	1
	M9000-534	VG2000 linkage kit for tandem M9124 Series electric actuators and Johnson Controls 5 in. cast iron globe valves with 1/2 in. stems	1
	M9000-536	VG2000 linkage kit for tandem M9124 Series electric actuators and Johnson Controls 6 in. cast iron globe valves with 1/2 in. stems	1
1000	M9000-537	VG2000 linkage kit for tandem M9124 Series electric actuators and Johnson Controls 3 to 4 in. cast iron globe valves with 1/2 in. stems	1
(M9000-534.til)			
	M9000-610	Tandem actuator adapter kit for VG2000 Series iron globe valve linkages (not for use with the M9000-530 linkage)	1
(M9000-610.tif)			

M9108, M9116, M9124, and M9132 Series Actuator Accessories (Part 4 of 4)

	Code Number	Description ¹	Qty
Weather Shields			
(M9000-310.47)	M9000-310	NEMA 3R weather shield for control dampers or M9000-53x linkage kits on VG2000 Series cast iron flanged globe valves	1
(M9000-330.01)	M9000-330	NEMA 3R weather shield for VG1000 Series non-spring-return ball valves with M9000-518 linkage	1
Wiring Accessories			
(M9000-105.8/)	M9000-105	Pluggable 3-terminal block	
Miscellaneous (Unique to M9108[16][24][32]	Series Actuators)		
	M9000-103	Transformer, Class 2, 120/24 VAC	1
(M9000-103.1I)	M9000-104	Transformer, Class 2, 230/24 VAC	1

1. Ø means round shaft size (diameter);

mutual means square shaft size (each side)

M(VA)9308 M(VA)9310 Series Actuator Accessories





Accessories (Order Separately) (Part 1 of 3)

	Code Number	Description	Qty
Damper Linkages / Accessories			
Res	DMPR-KC003	Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)	1
(M9000_400.jpg)	M9000-400	Jackshaft mounting kit, Ø 0.5 to 1.05 in.	1
Weather Shields			
(M9000. 32 1.jpg)	M9000-322	Weather shield NEMA 4x (IP66), for M9300 on dampers	1
	M9000-342	Weather shield NEMA4x (IP66), 1/2 to 2 in. for VA9300 on VG1000 Series ball valves	1

Accessories (Order Separately) (Part 2 of 3)

	Code Number	Description	Qty
Valve Linkages			
	M9000-561	Thermal barrier	1
	M9000-700	Universal Ball Valve Linkage Kit	1
(M9000_561.jpg) Mounting Brackets			
mounting Drackets	M9000-604	Anti-rotation bracket	1
(M9000_604.jpg)			
Shaft Couplers / Position Indicators			
0000	M9000-606	Position indicators, M9203, M9208, and M9300 Series	1
	M9300-2	Auxiliary Contact Kit	1
	M9300-100	Threaded Conduit Adapters for 1/2 in. electrician's fittings	5

Accessories (Order Separately) (Part 3 of 3)

	Code Number	Description	Qty
0	M9300-140	Feedback Potentiometer 140k ohms	1
BUILT SECTION	M9000-151	Remote mounting kit, with crank arm and damper linkage for M9108 (16) (24) Series Actuators	1
	M9300-1K	Feedback Potentiometer 1k ohms	1
	M9300-2K	Feedback Potentiometer 2k ohms	1
	M9300-10K	Feedback Potentiometer 10k ohms	1
	M9310-500	Replacement VA9308/9310 valve linkage kit	1
	M9310-600	Replacement M9308/9310 gripper assembly	1

Rotary Actuator Accessories Catalog Page (Continued) M(VA)9316, M(VA)9320 and M(VA)9335 Series Actuator Accessories





Accessories (Order Separately) (Part 1 of 3)

	Code Number	Description	Qty
Damper Linkages / Accessories		· ·	•
	DMPR-KC003	Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)	1
(M9000_400,jpg)	M9000-400	Jackshaft mounting kit, Ø 0.5 to 1.05 in.	1
Weather Shields			
	M9000-323	Weather shield NEMA 4x (IP66), for M9300 on dampers	1
(M9000_321,jpg)	M9000-343	Weather shield NEMA4x (IP66), 1/2 to 2 in. for M9300 on VG1000 Series ball valves	1
Valve Linkages			<u> </u>

Accessories (Order Separately) (Part 2 of 3)

	Code Number	Description	Qty
	M9000-539	Adapter for M9000-53x linkages	1
R			
(M9000_561.jpg)			
Mounting Brackets			1
(M9000_604,pg)	M9000-604	Anti-rotation bracket	1
	M9300-100D	Butterfly Valve Mounting Kit for Tandem M9300 Series Non-Spring Return Electric Actuators to 4, 5 and 6 in. (DN 100, 125 & 150)	1
	M9300-100S	Butterfly Valve Mounting Kit for a Single M9300 Series Non-Spring Return Electric Actuator to 2, 3 and 4 in. (DN 50, 80 & 100)	1
	M9300-200S	Butterfly Valve Mounting Kit for a Single M9300 Series Non-Spring Return Electric Actuator to 8 in. (DN 200)	1
Shaft Couplers / Position Indicators			
0000	M9000-606	Position indicators, M9203, M9208, and M9300 Series	1
M3002	M9300-2	Auxiliary Contact Kit	1

Accessories (Order Separately) (Part 3 of 3)

	Code Number	Description	Qty
	M9300-100	Threaded Conduit Adapters for 1/2 in. electrician's fittings	5
0.	M9300-140	Feedback Potentiometer 140k ohms	1
BOTTER CHI	M9000-151	Remote mounting kit, with crank arm and damper linkage for M9108 (16) (24) Series Actuators	1
0	M9300-1K	Feedback Potentiometer 1k ohms	1
0	M9300-2K	Feedback Potentiometer 2k ohms	1
0	M9300-10K	Feedback Potentiometer 10k ohms	1
	M9320-500	Replacement VA9320/9335 valve linkage kit	1
Q C	M9320-600	Replacement M9320/9335 gripper assembly	1

M(VA)9203 Series Actuator Accessories



M(VA)9203 Series Actuator Accessories (Part 1 of 4)

M(VA)9203 Series Actuator Accessor	Code Number	Description ¹	Qty
Shaft Couplers / Position Indicators			I
0000	M9000-606	Position indicators, M9203 and M9208 Series	5
	M9203-601	Standard coupler kit, M9203 Series (Ø 1/4 to 1/2 in.) (□ 1.4 to 5/16 in.)	1
(M3203_602.jpg)	M9203-602	Retainer for M9203 coupler	5
Mounting Brackets		•	•
(M9000_604,pg)	M9000-604	Anti-rotation bracket	1

M(VA)9203 Series Actuator Accessories (Part 2 of 4)

Code Number	Description ¹	Qty
I		
M9000-322	Weather shield NEMA 4x (IP66), control dampers	1
M0000 242	Weather shield NEMA 4x (IDSS), 1/2 to 2 in VC1000 Series hall	1
W9000-342	valves	1
		- 14
DMPR-KC003	(for use with D1300 dampers only)	1
DMPR-KC054	Damper blade arm (for use with D1300 dampers only)	1
DMPR-KC100	Damper blade linkage (for use with D1300 dampers only)	1
DMPR-KC102	Blade nin extension (Ø 1/2 x 7 in)	1
	(for use with D1300 dampers only)	
M9203-100	Remote mounting kit with crankarm	1
	M9000-322 M9000-342 M9000-342 DMPR-KC003 DMPR-KC054	M9000-322 Weather shield NEMA 4x (IP66), control dampers M9000-342 Weather shield NEMA 4x (IP66), 1/2 to 2 in. VG1000 Series ball valves DMPR-KC003 Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only) DMPR-KC054 Damper blade arm (for use with D1300 dampers only) DMPR-KC100 Damper blade linkage (for use with D1300 dampers only) DMPR-KC102 Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)

M(VA)9203 Series Actuator Accessories (Part 3 of 4)

Code Number	Description ¹	Qty
M9203-110	Universal mounting kit	1
M9203-115	Universal mounting kit with crankarm	1
M0202 150	Crankarn kit	1
110200-100		
M9203-250	D1300 dampers	1
		-
IM3000-602	Ball joint for Ø 1/4 and Ø 5/16 in. rods, 5/16-24 x 33/64 in. thread mount	5
M9203-603	Adjustable stop kit	1
	M9203-110 M9203-115 M9203-150 M9203-250 M9203-250	M9203-110 Universal mounting kit M9203-115 Universal mounting kit with crankarm M9203-150 Crankarm kit M9203-250 Remote mounting kit with crankarm and damper linkage for D1300 dampers M9203-250 Ball joint for Ø 1/4 and Ø 5/16 in. rods, 5/16-24 x 33/64 in. thread mount

M(VA)9203 Series Actuator Accessories (Part 4 of 4)

(VA)9203 Series Actuator Accessories	Code Number	Description ¹	Qty
alve Linkages			•
000	M9000-607	Position indicators, VA9203 and VA9208 Series	5
19000_607.jpg)			
	M9000-560	Ball valve linkage for spring return, 1/2 to 2 in. hot and chilled water applications	1
19000-560.jpg)	M9000-561	Thermal barrier	1
19000_561.jpg	M9000-700	Universal Ball Valve Linkage Kit	1
	Mianor-100		

1. Ø means round shaft size (diameter); □ means square shaft size (each side)

M(VA)9208 Series Actuator Accessories



M(VA)9208 Series Actuator Accessories (Part 1 of 3)

M(VA)9206 Selles Actuator Accessories	Code Number	Description ¹	Qty
Shaft Couplers / Position Indicators			
(M9000-600.01)	M9208-600	Large coupler kit for use with M9208 Series actuators (Ø 1/2 to 3/4 in. and \square 3/8 to 9/16 in.)	1
(M9000-601.87)	M9208-601	Standard coupler kit for use with M9208 Series actuators (Ø 5/16 to 5/8 in. and \square 1/4 to 1/2 in.)	1
(M9208-602.81)	M9208-602	Retainer for M9208 coupler	5
Mounting Brackets			
(M9000-604.8/)	M9000-604	Anti-rotation bracket	1
Tools	<u>_</u>		
(M9220-604.iif)	M9220-604	Long manual crank, 2-13/16 in. (72 mm) crank radius	5
	M9208-605	Short manual crank, 1-13/16 in. (47 mm) crank radius	5
(M3209-605.8/)	M9000-322	Weather shield NEMA 4X(IP66), control dampers	1
(M9000_321.jpg)			

M(VA)9208 Series Actuator Accessories (Part 2 of 3)

	Code Number	Description ¹	Qty
Neather Shields			
A A A A A A A A A A A A A A A A A A A	M9000-342	Weather shield NEMA 4X(IP66), 1/2 to 2 in. VG1000 Series ball valves	1
(M9000_341.jpg)			
Damper Linkages / Accessories			
	DMPR-KC003	Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)	1
DMPR-KC003 LII)	DMPR-KC054	Damper blade arm (for use with D1300 dampers only)	1
DMPR-KC054.11)	DMPR-KC100	Damper blade linkage (for use with D1300 dampers only)	1
DMPR-KC102.00	DMPR-KC102	Damper push rod, Ø 5/16 x 48 in.	1
1000	M9000-400	Jackshaft mounting kit, Ø 0.5 to 1.05 in.	
M8000_400,(pg)	M9000-402	Replacement hardware for M9000-400 jackshaft mounting kit	
M9000_402.(pg)	M9000-605	Ball joint for Ø 1/4 and Ø 5/16 in. rods, 5/16-24 x 33/64 in. thread mount	5
M8000.605.jpg	M9208-100	Remote mounting kit with crankarm	1

M(VA)9208 Series Actuator Accessories (Part 3 of 3)

	Code Number	Description ¹	Qty
amper Linkages / Accessories			
	M9208-150	Crankarm kit	1
19208-150.il)			
	M9208-250	Remote mounting kit with crankarm and damper linkage	1
		(for use with D1300 dampers only)	
M9208-250.tif)			
Adjustable Stops			
M9208-603.4/)	M9208-603	Adjustable stop kit	1
Viring Accessories			
•	M9200-100	Threaded conduit adapters for 1/2 in. electrician's fittings	1
66 8 8 BB			
M9200_100.jpg)			
/alve Linkages	M9000-607	Position indicators, VA9203 and VA9208 Series	5
000			
//9000_607.jpg)	M9000-560	Ball valve linkage for spring return	1
		Ball valve linkage for spring return, 1/2 to 2 in. hot and chilled water applications	
M9000-560.jpg)	N0000 504	Theorem howing	
	M9000-561	Thermal barrier	1
///9000_561.jpg			
	M9000-700	Universal Ball Valve Linkage Kit ²	1
1111 00000			

1. Ø means round shaft size (diameter); □ means square shaft size (each side)

2. For VA9208 Series Actuators: Use field furnished #10-24 x 3 1/2" screws and two locking nuts #10-24.

M9220 Series Actuator Accessories



(M9220-BAC-3.tif)

M9220 Series Actuator Accessories (Part 1 of 4)

M9220 Series Actuator Accessories	Code Number	Description ¹	Qty
Shaft Couplers / Position Indicators			
Ø	M9000-611	Position indicators for use with M9220 Series actuators	5
(M9000-611.tif)	M0000 000		4
(M9220-600A.HI)	M9220-600	Jackshaft coupler kit for use with M9220 Series actuators Ø 3/4 in. to 1-1/16 in. (19 to 27 mm) round shafts; or 5/8 and 3/4 in. (16, 18 and 19 mm) square shafts	1
	M9220-601	Standard coupler kit for use with M9220 Series actuators Ø 1/2 to 3/4 in. (12 to 19 mm) round shafts; or 3/8 and 1/2 in. (10, 12 and 14 mm) square shafts	1
(M9220-601.il)	M9220-602	Retainer for M9220 coupler	5
(M9220-602.tif)			
. 8 .	M9220-610 M9220-612	10 mm square shaft adapter with retainer 12 mm square shaft adapter with retainer	1
(M9220-602.tif)			
(wsz20~010.us)	M9220-614	14 mm square shaft adapter with retainer	1
Mounting Brackets			
	M9000-152	Reinforcing plate for mounting to thin sheet metal	1
(M9000-152.II)	M9000-158	Tandem mounting bracket	1

M9220 Series Actuator Accessories (Part 2 of 4)

M9220 Series Actuator Accessories (Part	Code Number Description ¹		Qty
	M9000-604	Anti -rotation bracket	1
8			
12 12			
(M9000-604.iif)			
Damper Linkages / Accessories			
	DMPR-KC003	Blade pin extension (Ø 1/2 x 7 in.) (for use with D1300 dampers only)	1
1			
DMPR-KC003.til)	DMPR-KC054	Damper blade arm (for use with D1300 dampers only)	1
			-
PB			
1000			
DMPR-KC054.uf)	DMPR-KC100	Damper blade linkage (for use with D1300 dampers only)	1
	DWFK-KC100	Damper brade linkage (for use with D1300 dampers only)	1
1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1			
Nº 430			
and a start			
(DMPR-KC100.tif)	DMPR-KC102	Damper push rod, Ø 5/16 x 48 in.	1
DMPR-KC102.tif)	DMPR-KC260	Damper mount linkage kit (for use with D1300 dampers only)	1
Real			
(DMPR-KC260.tif)			
	M9000-153	Crankarm kit (not for use with M9132 series actuators or tandem applications)	1
1 1 1			
(M9000-153.tif)			
mooo (outin)	M9000-170	Remote mounting kit (horizontal) with crankarm and ball joint	1
Vall			
\$11× //00*			
(M9000-170.tif)			
	M9000-171	Remote mounting kit (vertical) with crankarm and ball joint	1
P			
000			
///9000-171.iif)	M9000-270	Remote mounting kit (horizontal) with crankarm and damper	1
		linkage (for use with D1300 dampers only)	1
and the stee the			
(M-9000-270.til)			

M9220 Series Actuator Accessories (Part 3 of 4)

	Code Number	Description ¹	Qty
	M9000-271	Remote mounting kit (vertical) with crankarm and damper linkage (for use with D1300 dampers only)	1
	M9000-400	Jackshaft mounting kit, Ø 0.5 to 1.05 in.	1
1000			
19000_400.jpg)	M9000-402	Replacement hardware for M9000-400 jackshaft mounting kit	1
°°°°			
/9000_402.jpg)			
M9000_605.jpg)	M9000-605	Ball joint for Ø 1/4 and Ø 5/16 in. rods, 5/16-24 x 33/64 in. thread mount	5
	M9220-605	Ball joint for M8x1.25 threaded rod, M8x1.25 x 16.5 mm thread mount	5
/ag220-605.iif) /alve Linkages			
Me000-518.4/J	M9000-519	Ball valve linkage for spring return, 2-1/2 to 6 in. VG1000 flanged valves with 11 mm square stem	1
	M9000-530	VG2000 linkage kit for M9220 Series electric actuator and Johnson Controls 2-1/2 in. cast iron globe valves with 3/8 in. stems	1
	M9000-531	VG2000 linkage kit for a single M9220 Series electric actuator and Johnson Controls 3 in. and 4 in. cast iron globe valves with 3/8 in. stems	1
	M9000-533	VG2000 linkage kit for a single M9220 Series electric actuator and Johnson Controls 5 in. cast iron globe valves with 1/2 in. stems	
	M9000-535	VG2000 linkage kit for a single M9220 Series electric actuator and Johnson Controls 6 in. cast iron globe valves with 1/2 in. stems	1
M9000-531.tif)			

M9220 Series Actuator Accessories (Part 4 of 4)

	Code Number	Description ¹	Qty
-	M9000-532	VG2000 linkage kit for tandem M9220 Series electric actuators and Johnson Controls 3 in. and 4 in. cast iron globe valves with 3/8 in. stems	1
	M9000-534	VG2000 linkage kit for tandem M9220 Series electric actuators and Johnson Controls 5 in. cast iron globe valves with 1/2 in. stems	1
	M9000-536	VG2000 linkage kit for tandem M9220 Series electric actuators and Johnson Controls 6 in. cast iron globe valves with 1/2 in. stems	1
19000-535.III)	M9000-537	VG2000 linkage kit for tandem M9220 Series electric actuators and Johnson Controls 3 in. and 4 in. cast iron globe valves with 1/2 in. stems	1
111111111111	M9000-610	Tandem actuator adapter kit for VG2000 Series iron globe valve linkages (not for use with the M9000-530 linkage)	1
Veather Shields			
	M9000-320	NEMA 3R weather shield for control dampers or M9000-53x Series linkage kits on VG2000 Series cast iron flanged globe valves	1
M9000-320.ill)			
M9000-340.01)	M9000-340	NEMA 5 weather shield for VG1000 Series ball valves with M9000- 517 or M9000-519 linkage, spring return	1
Adjustable Stops			
M9220-603.if)	M9220-603	Adjustable stop kit	1
Wiring Accessories			
	M9200-100	Threaded conduit adapters for 1/2 in. electrician's fittings	
M9200_100.jpg)			
Fools	M9220-604	Manual crank	5
	WI9220-004	Ivianual Clarik	5

1. Ø means round shaft size (diameter);
□ means square shaft size (each side)

Miscellaneous Accessories

Miscellaneous Accessories

	Code Number	Description	Qty
Transformers			
(Y63722.00)	Y63T22-0	Transformer, 50 VA Class 2, 120/208/240 to 24 VAC 60 Hz, box mounting	1
Y63731.00	Y63T31-0	Transformer, 50 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot/box mounting	1
Y64T15.00)	Y64T15-0	Transformer, 92 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot mounting	1
Y6472 1.00)	Y64T21-0	Transformer, 92 VA Class 2, 120/208/240 to 24 VAC 60 Hz, box mounting	1
Y64T22.0()	Y64T22-0	Transformer, 92 VA Class 2, 120/208/240 to 24 VAC 60 Hz, box mounting	1
Y65A 13.00	Y65A13-0	Transformer, 40 VA Class 2, 120 to 24 VAC 60 Hz, foot mounting	1
Y65A21.00	Y65A21-0	Transformer, 40 VA Class 2, 120 to 24 VAC 60 Hz, box mounting	1
Y65G 13.00)	Y65G13-0	Transformer, 40 VA Class 2, 24 to 24 VAC 60 Hz isolation, foot mounting	1
Y655 13.00)	Y65S13-0	Transformer, 40 VA Class 2, 208/240 to 24 VAC 60 Hz, foot mounting	1
Y65T12.00	Y66T12-0	Transformer, 75 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot mounting	1
(Y66713.01)	Y66T13-0	Transformer, 75 VA Class 2, 120/208/240 to 24 VAC 60 Hz, foot mounting	1