

T-4054m

Energy Manager Heating-Cooling High Volume Output Thermostat

Description

The T-4054 Heating-Cooling, Energy Manager Thermostat is a high volume output, with an adjustable deadband of 0 to 30°F (0 to 16°C) between heating and cooling set points.

Refer to *T-4000 Series Pneumatic Room Thermostat Product Bulletin (LIT-7171060P)* for important product information.

Features

- available in Direct Acting (DIR) and Reverse Acting (REV) models
- includes Fahrenheit dial
- · mounts in vertical or horizontal position

Repair Information

If the T-4054 Heating-Cooling, Energy Manager Thermostat fails to operate within its specifications, replace the unit. For a replacement thermostat, contact the nearest Johnson Controls® representative.



T-4054 Heating-Cooling, Energy Manager Thermostat

Selection Charts

T-4054 Thermostat¹

Code Number	Description
T-4054-1	Direct Acting
T-4054-2	Reverse Acting

^{1.} Order cover and mounting bracket separately.

Commonly Used Accessories for T-4054 (Part 1 of 2)

Code		Description
Number		Description
T-4002-124		Room instrument mounting bracket for surface-mounting thermostats and covers; includes drywall clips, spacers, and mounting templates
T-4002-122		Terminal Connector, with two straight fittings for plug-in connection to 5/32 in. O.D. polyethylene tubing
T-4002-123	4	Terminal Connector, with angle fittings for surface mounted thermostats with exposed tubing
T-4002-5003	Pins	Restricted adjustment pin (100/kit) restricts adjustment of set point dial
T-4000-2138		Beige Plastic Cover, Horizontal or Vertical (no thermometer, no set point windows)
T-4000-2139	Johnson (M) Controls	Beige Plastic Cover, Horizontal (no thermometer, no set point windows)
T-4000-3139		White Plastic Cover, Horizontal (no thermometer, no set point windows)
T-4000-2140	Johnson (M) Controls	Beige Plastic Cover, Horizontal, thermometer (no set point windows)
T-4000-3140		White Plastic Cover, Horizontal, thermometer (no set point windows)
T-4756-2141	Johnson W Controls	Beige Plastic Cover, Horizontal, 2 set point windows (no thermometer)
T-4756-1738		Beige Plastic Cover, Horizontal, 2 set point windows with thermometer

Commonly Used Accessories for T-4054 (Part 2 of 2)

Commonly Used Accessories for 1-4054 (Part 2 of 2)				
Code Number		Description		
T-4000-2144		Beige Plastic Cover, Vertical (no thermometer, no set point windows)		
T-4000-3144	Jackmann All Cantrols	White Plastic Cover, Vertical (no thermometer, no set point windows)		
T-4756-2145	Judenzen @	Beige Plastic Cover, Vertical, 2 set point windows (no thermometer)		
T-4756-1739	Administration of the Control of the	Beige Plastic Cover, Vertical, 2 set point window with thermometer		

Note: For additional accessories, refer to T-4000 Series Accessories.

Technical Specifications

T-4054 Heating-Cooling, Energy Manager Thermostat			
Sensitivity	Adjustable from 1 to 3 psig/°F (12 to 38 kPa/°C) Factory set at approximately 2.5 psig/°F (32 kPa/°C)		
Flow Capacity	400 SCIM (107 mL/s)		
Air Consumption	38 SCIM (10 mL/s)		
Supply Pressure	13 to 25 psig (91 to 175 kPa) Nominal 20 psig (140 kPa)		
Dial Range	55 to 85°F (Two Dials)		
Air Connections	Two (Supply and Output)		
Deadband	Adjustable Deadband between 5 and 12 psig (35 to 84 kPa)		