

T-4756

Heating-Cooling High Volume Output Thermostats

Description

The T-4756 Thermostat is a high volume output, dual-temperature, dual-dial, heatingcooling thermostat. The T-4756 provides automatic changeover between direct and reverse actions when supply pressure changes from 15 to 20 psig (105 to 40 kPa).

Refer to T-4000 Series Pneumatic Room Thermostat Product Bulletin (LIT-7171060P) for important product information.

Features

- · includes Fahrenheit dial
- available in vertical or horizontal model

Repair Information

If the T-4756 Heating-Cooling High Volume Output Thermostat fails to operate within its specifications, replace the unit. For a replacement thermostat, contact the nearest Johnson Controls® representative.



T-4756 Heating-Cooling **High Volume Output Thermostat**

Selection Charts

T-4756 Heating-Cooling High Volume Output Thermostat¹

| Code Number | Description | | |
|-------------|---|--|--|
| T-4756-201 | 15 psig DIR, 20 psig REV, Horizontal Mounting | | |
| T-4756-202 | 15 psig DIR, 20 psig REV, Vertical Mounting | | |
| T-4756-205 | 15 psig REV, 20 DIR, Horizontal Mounting | | |
| T-4756-206 | 15 psig REV, 20 psig DIR, Vertical Mounting | | |

^{1.} Order cover and mounting bracket separately.

Commonly Used Accessories for T-4756 (Part 1 of 2)

| Code | | Description |
|-------------|-------------------------|---|
| Number | | Description |
| T-4002-124 | | Room instrument mounting bracket for surface-mounting thermostats and covers; includes drywall clips, spacers, and mounting templates |
| T-4002-122 | 4 | Terminal Connector, with two straight fittings for plug-in connection to 5/32 in. O.D. polyethylene tubing |
| T-4002-123 | 4 | Terminal Connector, with angle fittings for surface mounted thermostats with exposed tubing |
| T-4002-5003 | Pins | Restricted adjustment pin (100/kit) restricts adjustment of set point dial |
| T-4002-5012 | | Adjusting knob kit provides a means of external setpoint adjustment |
| T-4000-2138 | | Beige Plastic Cover, Horizontal or Vertical (no thermometer, no set point windows) |
| T-4000-2139 | Johnson (M) Controls | Beige Plastic Cover, Horizontal (no thermometer, no set point windows) |
| T-4000-3139 | | White Plastic Cover, Horizontal (no thermometer, no set point windows) |
| T-4000-2140 | Johnson (M) Controls | Beige Plastic Cover, Horizontal, thermometer (no set point windows) |
| T-4000-3140 | | White Plastic Cover, Horizontal, thermometer (no set point windows) |

| Commonly U | Commonly Used Accessories for T-4756 (Part 2 of 2) | | | | |
|----------------|--|--|--|--|--|
| Code Number | | Description | | | |
| T-4756-2141 | Johnson (Market) | Beige Plastic Cover, Horizontal, 2 set point windows (no thermometer) | | | |
| T-4756-1738 | Johnson Controls | Beige Plastic Cover, Horizontal, 2 set point windows with thermometer | | | |
| T-4000-2144 | | Beige Plastic Cover, Vertical (no thermometer, no set point windows) | | | |
| T-4000-3144 | Johnson (P) Controls | White Plastic Cover, Vertical (no thermometer, no set point windows) | | | |
| T-4756-2145 | Andream (Sp.) | Beige Plastic Cover, Vertical, 2 set point windows (no thermometer) | | | |
| T-4756-1739 | Jacobian (Marchaella Controls) | Beige Plastic Cover, Vertical, 2 set point window with thermometer | | | |

Note: For additional accessories, refer to T-4000 Series Accessories Catalog Page (LIT-1921710) on Page 94.

Technical Specifications

| T-4756 Heating-Cooling High Volume Output Thermostat | | | |
|--|--|--|--|
| Sensitivity | Adjustable from .75 to 4.0 psig/°F (9 to 50 kPa/°C) Factory set at approximately 2.5 psig/°F (32 kPa/°C) | | |
| Flow Capacity | 400 SCIM (107 mL/s) | | |
| Air Consumption | 20 SCIM (5 mL/s) | | |
| Supply Pressure | 13 to 25 psig (91 to 175 kPa) 15 psig (105 kPa) 20 psig (140 kPa) | | |
| Dial Range | 55 to 85°F (Two Dials) | | |
| Air Connections | Two (Supply and Output) | | |
| Special Feature | Dual Dials, separate set point adjustments | | |