



## Datasheet

# Differential Pressure Sensor (PL-MLP2-1.5-5)

## Description

The MLP2 Low Differential Pressure transmitters is designed for use in OEM or high density panel mounting applications. Key installation features include an integral 35 mm Din rail mounting foot, vertically orientated wiring and pressure connections, and a pushbutton zero function conveniently located on the front cover. The MLP2 incorporates a high accuracy, piezoresistive, silicon sensing element which senses differential pressure and provides a linear 4 to 20 mA or DC voltage output equal to the specified pressure range. This technology reduces warmup shift while also reducing the effect of package stress for increased long term stability. In addition, the unit contains a de-pluggable terminal block that can be removed for ease of installation.

## Features

- Removable terminal blocks
- Push button Auto Zero
- User adjustable Zero and Span
- Diagnostic Mode, Factory Reset
- Compact Size

## Technical Specifications

- **Supply Voltage:** 24 VAC ( $\pm 10\%$ ), 12-36 VDC
- **Supply Current:** 23 mA minimum
- **Output Voltage:** 0-5 VDC
- **Differential Pressure Range:** 0-1.5" w.c.
- **Accuracy<sup>1</sup>:**  $\pm 5\%$  FSO
- **Repeatability:**  $\pm 0.3\%$  FSO nominal
- **Temperature:** 32 to 185 °F (0 to 85 °C)
- **Humidity:** 10 to 95% RH, non-condensing
- **Media:** Dry air or inert non-conductive gases
- **Dimensions:** 4" x 3" x 1" (102 mm x 76 mm x 25 mm)
- **Weight:** 0.15 lbs (0.07 kg)
- **Enclosure:** Polycarbonate – UL94-V0
- **Approvals:** REACH, RoHS, WEEE

*Note<sup>1</sup>: Accuracy includes Hysteresis, Linearity, and Repeatability at 71°F (21.5°C) Typical*

## Dimensions in inches (mm)

