

Saginaw Control and Engineering 95 Midland Road Saginaw, MI 48638-5770 (800) 234-6871 - Fax: (989) 799-4524 SCE@SaginawControl.com

SCE-1816FW

Construction

- Fiberglass reinforced compression molded polyester. Ф
- Continuous memory retaining gasket. Mounting strips molded in. ¢
- Ф
- Quick release padlock latch. Ф
- ¢ Integral panel mounting inserts.
- Stainless steel continuous hinge ¢
- ¢ UVA acrylic bonded polycarbonate window.

Application

Designed for indoor or outdoor use to house electronic controls, instruments and components in areas that may be regularly hosed down, are in very wet conditions, or are exposed to corrosive agents and require unrestricted viewing of gauges or controls. Provides protection from dust, dirt, oil, and water.

Finish

Light gray fiberglass. Optional sub-panels are marine grade aluminum.

Industry Standards - (IS5)

- NEMA Type 4, 4X, 12 and Type 13
 UL Listed Type 4, 4X and 12
- ٥ CSA Type 4, 4X and 12
- IEC 60529 ¢
- ¢. IP 66

Notes

UL File E64358

Product Specifications:

Part Number: SCE-1816FW Description: Fiberglass Enclosure W/Window Height: 19.61" Width: 17.61" Depth: 8.82" Price Code: F1 List Price: \$524.97 Catalog Page: 338 Est. Ship Weight: 20.00 lbs

Optional Accessories

SCE-18P16AL Subpanel, Flat Aluminum

Similar Part Numbers

SCE-10086FWFiberglass Enclosure W/Window SCE-1008FWFiberglass Enclosure W/Window SCE-1407FWFiberglass Enclosure W/Window SCE-1407FWFiberglass Enclosure W/Window SCE-1412FWFiberglass Enclosure W/Window SCE-1614FWFiberglass Enclosure W/Window SCE-2016FWFiberglass Enclosure W/Window SCE-806FWFiberglass Enclosure W/Window SCE-808FWFiberglass Enclosure W/Window