



Your Enclosure Source®

Saginaw Control and Engineering  
95 Midland Road Saginaw, MI 48638-5770  
(800) 234-6871 - Fax: (989) 799-4524  
SCE@SaginawControl.com

## SCE-30EL2412SS6LPPL



## Product Specifications:

**Part Number:** SCE-30EL2412SS6LPPL  
**Description:** S.S. LPPL Enclosure  
**Height:** 30.00"  
**Width:** 24.00"  
**Depth:** 12.00"  
**Price Code:** S9  
**List Price:** \$1,744.88  
**Catalog Page:** 272  
**Est. Ship Weight:** 79.20 lbs

### Construction

- \* 0.075 In. stainless steel Type 316/316L.
- \* Seams continuously welded and ground smooth.
- \* Flange trough collar around all sides of door opening
- \* Collar studs 3/8-16 provided for mounting optional panels.
- \* Mounting holes in back of enclosure for wall mounting.
- \* Mounting hardware, sealing washer and hole plug included.
- \* Stainless steel concealed hinges.
- \* Removable and interchangeable doors.
- \* Black zinc die cast keylocking/padlocking handle.
- \* 3-point latching mechanism.
- \* Removable print pocket.
- \* Pour in place oil & water resistant gasket
- \* Ground stud on door and body.

### Application

Designed to house electrical and electronic controls, instrumentation and components in indoor or outdoor locations. For outdoor applications a drip shield is recommended. For outdoor application a drip shield is recommended.

For Details about the Design, Performance Expectations, Applications and Design Suggestions - See Design Considerations  
[www.saginawcontrol.com/instman/considerations.pdf](http://www.saginawcontrol.com/instman/considerations.pdf)

### Finish

#4 Brushed finish on all exterior surfaces.  
Optional sub-panels are powder coated white.

### Industry Standards - (IS6)

- \* NEMA Type 3R, 4, 4X, 12 and Type 13
- \* UL Listed Type 3R, 4, 4X and 12
- \* CSA Type 4, 4X and 12
- \* IEC 60529
- \* IP 66

### Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

Provision for Lifting Lugs on enclosures when Height >48" and Depth >16".  
The Lifting Lug assembly will be included with the enclosure bolt pack.

### Optional Accessories

- SCE-30P24 Subpanel, Bent
- SCE-30P24GALV Subpanel, Bent Galvanized
- SCE-BVK Breather Vent
- SCE-DF30EL24LP Panel, Dead Front (Wall Mount)
- SCE-DS24SS Shield, S.S. Drip
- SCE-ELFM24WSS S.S. EL Flush Mount Frame
- SCE-ELFM30HSS S.S. EL Flush Mount Frame
- SCE-ELMFK4SS6-OS Foot Kit, S.S. EL Mounting (4pc.)
- SCE-ELSP3 KIT, Swing-Out Panel (20 High & Up)
- SCE-RD30EL24SS6LPPL Door, Replacement

### Similar Part Numbers

- SCE-24EL2010SS6LPPLS.S. LPPL Enclosure
- SCE-24EL2410SS6LPPLS.S. LPPL Enclosure
- SCE-30EL3012SS6LPPLS.S. LPPL Enclosure
- SCE-36EL2412SS6LPPLS.S. LPPL Enclosure
- SCE-36EL3012SS6LPPLS.S. LPPL Enclosure
- SCE-42EL3612SS6LPPLS.S. LPPL Enclosure

### Installation Information

- \* Sealing Washer Specifications
- \* Dead Front Wall Mount With 3 Point Latching Hardware
- \* EL Flush Mount Frame
- \* Dead Front Wall Mount Installation Instructions
- \* Swing Panel ELSP3 for Encl. Height > 16
- \* Drip Shield Kit Assembly
- \* Service Parts Wall Mount Disconnect Enclosures