



### Main

Product or component type	Single Throw Safety Switch
Series name	General duty

### Complementary

Device composition	Neutral (factory installed)
Disconnecter device type	Fusible disconnect
Short-circuit current	100 kA maximum cartridge
Device mounting	Surface
Number of poles	3
Electrical connection	Lugs
[Ue] rated operational voltage	120/240 V AC
AWG gauge	AWG 14...AWG 3 copper or aluminum
Motor power hp	7.5 hp 240 V AC 50...60 Hz 1 phase NEC 240.6 15 hp 240 V AC 50...60 Hz 3 phases NEC 240.6 15 hp 240 V AC 50...60 Hz 1 phase NEC 430.52 30 hp 240 V AC 50...60 Hz 3 phases NEC 430.52
Width	7.45 in (189.23 mm)
Height	14.88 in (377.95 mm)
Depth	4.87 in (123.70 mm)
Tightening torque	35 lbf.in (3.95 N.m) 0.00...0.01 in <sup>2</sup> (2.08...5.26 mm <sup>2</sup> ) AWG 14...AWG 10) 45 lbf.in (5.08 N.m) 0.01 in <sup>2</sup> (8.37 mm <sup>2</sup> ) AWG 8) 45 lbf.in (5.08 N.m) 0.02...0.03 in <sup>2</sup> (12.3...21.12 mm <sup>2</sup> ) AWG 6...AWG 4) 50 lbf.in (5.65 N.m) 0.04 in <sup>2</sup> (26.67 mm <sup>2</sup> ) AWG 3)

### Environment

Product certifications	CSA
NEMA degree of protection	NEMA 3R galvanized steel

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

**Offer Sustainability**

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>