

Pneumatic Tube Fitting Kit



141-0601 Pneumatic Tube Fitting Kit.



141-464 Case.

Description

The Pneumatic Tube Fitting Kit provides the service or installation mechanic with a compact and convenient source of the most commonly used brass barbed fittings for 1/4-inch (6 mm), 3/8-inch (10 mm) and 1/2-inch (13 mm) OD polyethylene tubing.

Features

- Rustproof, odor and oil resistant case
- Translucent lid for easy identification of fittings
- Double positive latches
- 15 dividers for configuring up to 24 compartments
- Lower cost for fittings
- Representative quantities of commonly used 1/4-inch (6 mm), 3/8-inch (10 mm) and 1/2-inch (13 mm) brass fittings

Applications

The Pneumatic Tube Fitting Kit is useful for servicing, modifying, or adding to pneumatic control systems. Purchasing in quantity reduces material costs. Labor savings is the major reason to have this convenient kit in your service shop or van.

F-49












Pneumatics

Pneumatic Tube Fitting Kit Specifications

Case MaterialCopolymer Resin
Dimensions 15" L x 11.75" W x 2.5" D
(381 mm L x 298 mm W x 64 mm D)
Shipping Weight
Case3.0 lb. (1.4 kg)
Case and Fittings7.0 lb. (3.2 kg)

Other Supplies and Equipment
The fittings in this kit represent most of the commonly used polyethylene tube fittings required by HVAC mechanics.

Kit Includes:

	Description	Quantity
	Barbed Tee.	
	• 1/4" (6 mm)	12
	• 3/8" (10 mm)	6
	• 1/2" (13 mm)	6
	1/4" (6 mm) Barbed Reducing Tee.	
	• 3/8" (10 mm)	6
	• 1/2" (13 mm)	6
	90° Elbow.	
	• 1/4" (6 mm)	12
	• 3/8" (10 mm)	6
	• 1/2" (13 mm)	6
	1/8" NPT Male x 90° Elbow.	
	• 1/4" (6 mm) or 5/32" (4 mm)	12
	1/4" (6 mm) OD Copper Coupling.	
	• 1/4" (6 mm)	10
	1/8" NPT Male.	
	• 1/4" (6 mm)	10
	Gauge Tee 1/8" NPT Male/NPT Female.	
	• 1/4" (6 mm)	10
	Gauge Tee 1/8" NPT Female.	
	• 1/4" (6 mm)	5
	Plug.	
	• 1/4" (6 mm)	10
	Reducer Coupling OD.	
	• 1/4" (6 mm)	10
	Coupling.	
	• 1/4" (6 mm)	12
	• 3/8" (10 mm)	10
	• 1/2" (13 mm)	10