

Two-Way **Globe** Valve Assemblies

ANSI Class 250

Electronic Non-Spring Return Actuators

- Normally Open or Normally Closed
- Linear
- Stainless Steel Trim



NO/NC Linear 1/2 to 2"			Non-Spring Return Actuator							
			Floating 3P	Floating 3P	0-10 Vdc 4-20 mA	0-10 Vdc 4-20 mA				
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv				 NEW!				
			SAX81.03U	SKD82.50U	SAX61.03U	SKD60U				
Normally Open										
			Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)							
	1/2	1	250	373-03000	250	275-03000	250	371-03000	250	267-03000
		1.6	250	373-03001	250	275-03001	250	371-03001	250	267-03001
		2.5	250	373-03002	250	275-03002	250	371-03002	250	267-03002
		4	250	373-03003	250	275-03003	250	371-03003	250	267-03003
	3/4	6.3	211	373-03004	250	275-03004	211	371-03004	250	267-03004
	1	10	137	373-03005	201	275-03005	137	371-03005	201	267-03005
	1-1/4	16	85	373-03006	124	275-03006	85	371-03006	124	267-03006
	1-1/2	25	55	373-03007	80	275-03007	55	371-03007	80	267-03007
	2	40	34	373-03008	49	275-03008	34	371-03008	49	267-03008
	Close-off psi — High-temperature Range is 337° F max. (170° C)									
	1/2	1	—	250	275-03054	—	250	267-03054		
		1.6	—	250	275-03055	—	250	267-03055		
		2.5	—	250	275-03056	—	250	267-03056		
		4	—	250	275-03057	—	250	267-03057		
	3/4	6.3	—	250	275-03058	—	250	267-03058		
	1	10	—	201	275-03059	—	201	267-03059		
	1-1/4	16	—	124	275-03060	—	124	267-03060		
1-1/2	25	—	80	275-03061	—	80	267-03061			
2	40	—	49	275-03062	—	49	267-03062			
Normally Closed										
			Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)							
	1/2	1	250	373-03018	250	275-03018	250	371-03018	250	267-03018
		1.6	250	373-03019	250	275-03019	250	371-03019	250	267-03019
		2.5	250	373-03020	250	275-03020	250	371-03020	250	267-03020
		4	250	373-03021	250	275-03021	250	371-03021	250	267-03021
	3/4	6.3	250	373-03022	250	275-03022	250	371-03022	250	267-03022
	1	10	159	373-03023	203	275-03023	159	371-03023	203	267-03023
	1-1/4	16	92	373-03024	117	275-03024	92	371-03024	117	267-03024
	1-1/2	25	57	373-03025	73	275-03025	57	371-03025	73	267-03025
	2	40	35	373-03026	44	275-03026	35	371-03026	44	267-03026
	Close-off psi — High-temperature Range is 337° F max. (170° C)									
	1/2	1	—	250	275-03072	—	250	267-03072		
		1.6	—	250	275-03073	—	250	267-03073		
		2.5	—	250	275-03074	—	250	267-03074		
		4	—	250	275-03075	—	250	267-03075		
	3/4	6.3	—	250	275-03076	—	250	267-03076		
	1	10	—	203	275-03077	—	203	267-03077		
	1-1/4	16	—	117	275-03078	—	117	267-03078		
1-1/2	25	—	73	275-03079	—	73	267-03079			
2	40	—	44	275-03080	—	44	267-03080			

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.