

Three-Way **Globe** Valve Assemblies

ANSI Class 250

Electronic Non-Spring Return Actuators

- Brass and Stainless Steel Trim

Flowrite Selection Tables



Mixing 1/2 to 2"			Non-Spring Return Actuator			
			Floating 3P	Floating 3P	0-10 Vdc 4-20 mA	0-10 Vdc 4-20 mA
3-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	 SAX81.03U	 SKD82.50U	 SAX61.03U	 SKD60U
			Close-off psi — Brass Trim			
599-03198	1/2	1	250 373-03198	250 275-03198	250 371-03198	250 267-03198
599-03199		1.6	250 373-03199	250 275-03199	250 371-03199	250 267-03199
599-03200		2.5	250 373-03200	250 275-03200	250 371-03200	250 267-03200
599-03201		4	250 373-03201	250 275-03201	250 371-03201	250 267-03201
599-03202	3/4	6.3	250 373-03202	250 275-03202	250 371-03202	250 267-03202
599-03203	1	10	159 373-03203	203 275-03203	159 371-03203	203 267-03203
599-03204	1-1/4	16	92 373-03204	117 275-03204	92 371-03204	117 267-03204
599-03205	1-1/2	25	57 373-03205	73 275-03205	57 371-03205	73 267-03205
599-03206	2	40	35 373-03206	44 275-03206	35 371-03206	44 267-03206
			Close-off psi — Stainless Steel Trim			
599-03144	1/2	1	250 373-03144	250 275-03144	250 371-03144	250 267-03144
599-03145		1.6	250 373-03145	250 275-03145	250 371-03145	250 267-03145
599-03146		2.5	250 373-03146	250 275-03146	250 371-03146	250 267-03146
599-03147		4	250 373-03147	250 275-03147	250 371-03147	250 267-03147
599-03148	3/4	6.3	250 373-03148	250 275-03148	250 371-03148	250 267-03148
599-03149	1	10	159 373-03149	203 275-03149	159 371-03149	203 267-03149
599-03150	1-1/4	16	92 373-03150	117 275-03150	92 371-03150	117 267-03150
599-03151	1-1/2	25	57 373-03151	73 275-03151	57 371-03151	73 267-03151
599-03152	2	40	35 373-03152	44 275-03152	35 371-03152	44 267-03152

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.

Values are for the NC upper port. For NO lower port values, refer to Engineering, Section G.

A-37

Valves