

Two-Way Flanged **Globe** High Pressure Close-off Valve Assemblies

ANSI Class 250

Pneumatic and Electro-Hydraulic Spring Return Actuators

- Normally Open or Normally Closed
- Equal Percentage
- Stainless Steel Trim
- Pressure Balanced Plug
- 200 psi Close-off



NO/NC Equal Percentage Flanged 2-1/2 to 6"				Spring Return Actuator				
				8" w/ Positioner 20 mm Stroke	12" w/ Positioner 40 mm Stroke	0-10 Vdc 4-20 mA	0-10 Vdc 4-20 mA	
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	Close Off psi	 599-01050 + 599-00426	 599-01000 + 599-00423	 SKD62U	 SKC62U	
Normally Open								
				Stainless Steel Trim				
	599-06620	2-1/2	63	200	283-06620	—	274-06620	—
	599-06621	3	100	200	283-06621	—	274-06621	—
	599-06622	4	160	200	—	287-06622	—	294-06622
	599-06623	5	250	200	—	287-06623	—	294-06623
599-06624	6	400	200	—	287-06624	—	294-06624	
Normally Closed								
				Stainless Steel Trim				
	599-06625	2-1/2	63	200	283-06625	—	274-06625	—
	599-06626	3	100	200	283-06626	—	274-06626	—
	599-06627	4	160	200	—	287-06627	—	294-06627
	599-06628	5	250	200	—	287-06628	—	294-06628
599-06629	6	400	200	—	287-06629	—	294-06629	

Table Notes:

Part numbers in red indicate complete assemblies.

Close-off values are for 15 psi signal for Normally Open and 0 psi signal for Normally Closed.

A-47

Valves