

Two-Way Flanged **Globe** Valve Assemblies

ANSI Class 125

Electronic Spring Return Actuators

- Normally Open or Normally Closed
- Equal Percentage
- Bronze and Stainless Steel Trim



NO/NC Equal Percentage Flanged 2-1/2 to 6"			Spring Return Actuator					
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	Floating 3P	Floating 3P	Floating 3P	0-10 Vdc 4-20 mA	0-10 Vdc 4-20 mA	0-10 Vdc 4-20 mA
								
			SKD82.51U	SKB82.51U	SKC82.61U	SKD62U	SKB62U	SKC62U
Normally Open			Close-off psi — Bronze Trim					
	599-05980	2-1/2 63	38 276-05980	153 289-05980	—	38 274-05980	153 291-05980	—
	599-05981	3 100	25 276-05981	101 289-05981	—	25 274-05981	101 291-05981	—
	599-05982	4 160	—	—	65 292-05982	—	—	65 294-05982
	599-05983	5 250	—	—	42 292-05983	—	—	42 294-05983
	599-05984	6 400	—	—	29 292-05984	—	—	29 294-05984
			Close-off psi — Stainless Steel Trim					
	599-05960	2-1/2 63	38 276-05960	153 289-05960	—	38 274-05960	153 291-05960	—
	599-05961	3 100	25 276-05961	101 289-05961	—	25 274-05961	101 291-05961	—
	599-05962	4 160	—	—	65 292-05962	—	—	65 294-05962
	599-05963	5 250	—	—	42 292-05963	—	—	42 294-05963
	599-05964	6 400	—	—	29 292-05964	—	—	29 294-05964
Normally Closed			Close-off psi — Bronze Trim					
	599-05990	2-1/2 63	34 276-05990	97 289-05990	—	34 274-05990	97 291-05990	—
	599-05991	3 100	22 276-05991	63 289-05991	—	22 274-05991	63 291-05991	—
	599-05992	4 160	—	—	39 292-05992	—	—	39 294-05992
	599-05993	5 250	—	—	25 292-05993	—	—	25 294-05993
	599-05994	6 400	—	—	17 292-05994	—	—	17 294-05994
			Close-off psi — Stainless Steel Trim					
	599-05970	2-1/2 63	34 276-05970	97 289-05970	—	34 274-05970	97 291-05970	—
	599-05971	3 100	22 276-05971	63 289-05971	—	22 274-05971	63 291-05971	—
	599-05972	4 160	—	—	39 292-05972	—	—	39 294-05972
	599-05973	5 250	—	—	25 292-05973	—	—	25 294-05973
	599-05974	6 400	—	—	17 292-05974	—	—	17 294-05974

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.

A-39

Valves