

Two-Way Flanged **Globe** Valve Assemblies

ANSI Class 250

Electronic Spring Return Actuators

- Normally Open or Normally Closed
- Linear
- Stainless Steel Trim



A-52

Valves

NO/NC Linear Flanged 2-1/2 to 6"			Spring Return Actuator					
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	Floating 3P	Floating 3P	Floating 3P	0-10 Vdc 4-20 mA	0-10 Vdc 4-20 mA	0-10 Vdc 4-20 mA
			SKD82.51U	SKB82.51U	SKC82.61U	SKD62U	SKB62U	SKC62U
Normally Open			Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)					
599-06140	2-1/2	63	38 276-06140	153 289-06140	—	38 274-06140	153 291-06140	—
599-06141	3	100	25 276-06141	101 289-06141	—	25 274-06141	101 291-06141	—
599-06142	4	160	—	—	65 292-06142	—	—	65 294-06142
599-06143	5	250	—	—	42 292-06143	—	—	42 294-06143
599-06144	6	400	—	—	29 292-06144	—	—	29 294-06144
			Close-off psi — High-temperature Range is 337° F max. (170° C)					
599-06120	2-1/2	63	38 276-06120	153 289-06120	—	38 274-06120	153 291-06120	—
599-06121	3	100	25 276-06121	101 289-06121	—	25 274-06121	101 291-06121	—
599-06122	4	160	—	—	65 292-06122	—	—	65 294-06122
599-06123	5	250	—	—	42 292-06123	—	—	42 294-06123
599-06124	6	400	—	—	29 292-06124	—	—	29 294-06124
Normally Closed			Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)					
599-06150	2-1/2	63	34 276-06150	97 289-06150	—	34 274-06150	97 291-06150	—
599-06151	3	100	22 276-06151	63 289-06151	—	22 274-06151	63 291-06151	—
599-06152	4	160	—	—	39 292-06152	—	—	39 294-06152
599-06153	5	250	—	—	25 292-06153	—	—	25 294-06153
599-06154	6	400	—	—	17 292-06154	—	—	17 294-06154
			Close-off psi — High-temperature Range is 337° F max. (170° C)					
599-06130	2-1/2	63	34 276-06130	97 289-06130	—	34 274-06130	97 291-06130	—
599-06131	3	100	22 276-06131	63 289-06131	—	22 274-06131	63 291-06131	—
599-06132	4	160	—	—	39 292-06132	—	—	39 294-06132
599-06133	5	250	—	—	25 292-06133	—	—	25 294-06133
599-06134	6	400	—	—	17 292-06134	—	—	17 294-06134

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.