

Two-Way Flanged **Globe** Valve Assemblies

ANSI Class 250

Electronic Non-Spring Return Actuators

- Normally Open or Normally Closed
- Equal Percentage
- Bronze and Stainless Steel Trim



NO/NC Equal Percentage Flanged 2-1/2 to 6"			Non-Spring Return Actuator			
			Floating 3P	Floating 3P	Floating 3P	0-10 Vdc 4-20 mA
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv				 NEW!
Normally Open						
Close-off psi — Bronze Trim						
599-05940	2-1/2	63	38 275-05940	153 290-05940	—	38 267-05940
599-05941	3	100	25 275-05941	101 290-05941	—	25 267-05941
599-05942	4	160	—	—	65 293-05942	—
599-05943	5	250	—	—	42 293-05943	—
599-05944	6	400	—	—	29 293-05944	—
Close-off psi — Stainless Steel Trim						
599-05920	2-1/2	63	38 275-05920	153 290-05920	—	38 267-05920
599-05921	3	100	25 275-05921	101 290-05921	—	25 267-05921
599-05922	4	160	—	—	65 293-05922	—
599-05923	5	250	—	—	42 293-05923	—
599-05924	6	400	—	—	29 293-05924	—
Normally Closed						
Close-off psi — Bronze Trim						
599-05950	2-1/2	63	34 275-05950	97 290-05950	—	34 267-05950
599-05951	3	100	22 275-05951	63 290-05951	—	22 267-05951
599-05952	4	160	—	—	39 293-05952	—
599-05953	5	250	—	—	25 293-05953	—
599-05954	6	400	—	—	17 293-05954	—
Close-off psi — Stainless Steel Trim						
599-05930	2-1/2	63	34 275-05930	97 290-05930	—	34 267-05930
599-05931	3	100	22 275-05931	63 290-05931	—	22 267-05931
599-05932	4	160	—	—	39 293-05932	—
599-05933	5	250	—	—	25 293-05933	—
599-05934	6	400	—	—	17 293-05934	—

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.