

Two-Way Flanged **Globe** Valve Assemblies

ANSI Class 125

Electronic Non-Spring Return Actuators

- Normally Open or Normally Closed
- Equal Percentage
- Bronze and Stainless Steel Trim



NO/NC Equal Percentage Flanged 2-1/2 to 6"			Non-Spring Return Actuator			
			Floating 3P	Floating 3P	Floating 3P	0-10 Vdc 4-20 mA
						
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	SKD82.50U	SKB82.50U	SKC82.60U	SKD60U
Normally Open						
Close-off psi — Bronze Trim						
599-05980	2-1/2	63	38 275-05980	153 290-05980	—	38 267-05980
599-05981	3	100	25 275-05981	101 290-05981	—	25 267-05981
599-05982	4	160	—	—	65 293-05982	—
599-05983	5	250	—	—	42 293-05983	—
599-05984	6	400	—	—	29 293-05984	—
Close-off psi — Stainless Steel Trim						
599-05960	2-1/2	63	38 275-05960	153 290-05960	—	38 267-05960
599-05961	3	100	25 275-05961	101 290-05961	—	25 267-05961
599-05962	4	160	—	—	65 293-05962	—
599-05963	5	250	—	—	42 293-05963	—
599-05964	6	400	—	—	29 293-05964	—
Normally Closed						
Close-off psi — Bronze Trim						
599-05990	2-1/2	63	34 275-05990	97 290-05990	—	34 267-05990
599-05991	3	100	22 275-05991	63 290-05991	—	22 267-05991
599-05992	4	160	—	—	39 293-05992	—
599-05993	5	250	—	—	25 293-05993	—
599-05994	6	400	—	—	17 293-05994	—
Close-off psi — Stainless Steel Trim						
599-05970	2-1/2	63	34 275-05970	97 290-05970	—	34 267-05970
599-05971	3	100	22 275-05971	63 290-05971	—	22 267-05971
599-05972	4	160	—	—	39 293-05972	—
599-05973	5	250	—	—	25 293-05973	—
599-05974	6	400	—	—	17 293-05974	—

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.

A-40

Valves