

Two-Way Flanged **Globe** Valve Assemblies

ANSI Class 125

Electronic Non-Spring Return Actuators

- Normally Open or Normally Closed
- Linear
- Stainless Steel Trim



NO/NC Linear Flanged 2-1/2 to 6"			Non-Spring Return Actuator			
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	Floating 3P	Floating 3P	Floating 3P	0-10 Vdc 4-20 mA
			 SKD82.50U	 SKB82.50U	 SKC82.60U	 SKD60U NEW!
Normally Open						
Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)						
599-06060	2-1/2	63	38 275-06060	153 290-06060	—	38 267-06060
599-06061	3	100	25 275-06061	101 290-06061	—	25 267-06061
599-06062	4	160	—	—	65 293-06062	—
599-06063	5	250	—	—	42 293-06063	—
599-06064	6	400	—	—	29 293-06064	—
Close-off psi — High-temperature Range is 337° F max. (170° C)						
599-06040	2-1/2	63	38 275-06040	153 290-06040	—	38 267-06040
599-06041	3	100	25 275-06041	101 290-06041	—	25 267-06041
599-06042	4	160	—	—	65 293-06042	—
599-06043	5	250	—	—	42 293-06043	—
599-06044	6	400	—	—	29 293-06044	—
Normally Closed						
Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)						
599-06070	2-1/2	63	34 275-06070	97 290-06070	—	34 267-06070
599-06071	3	100	22 275-06071	63 290-06071	—	22 267-06071
599-06072	4	160	—	—	39 293-06072	—
599-06073	5	250	—	—	25 293-06073	—
599-06074	6	400	—	—	17 293-06074	—
Close-off psi — High-temperature Range is 337° F max. (170° C)						
599-06050	2-1/2	63	34 275-06050	97 290-06050	—	34 267-06050
599-06051	3	100	22 275-06051	63 290-06051	—	22 267-06051
599-06052	4	160	—	—	39 293-06052	—
599-06053	5	250	—	—	25 293-06053	—
599-06054	6	400	—	—	17 293-06054	—

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.

A-43

Valves