

Two-Way Flanged **Globe** Valve Assemblies

ANSI Class 250

Electronic Non-Spring Return Actuators

- Normally Open or Normally Closed
- Linear
- Stainless Steel Trim



NO/NC Linear Flanged 2-1/2 to 6"			Non-Spring Return Actuator			
2-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	Floating 3P	Floating 3P	Floating 3P	0-10 Vdc 4-20 mA
			 SKD82.50U	 SKB82.50U	 SKC82.60U	 SKD60U NEW!
Normally Open						
Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)						
599-06140	2-1/2	63	38 275-06140	153 290-06140	—	38 267-06140
599-06141	3	100	25 275-06141	101 290-06141	—	25 267-06141
599-06142	4	160	—	—	65 293-06142	—
599-06143	5	250	—	—	42 293-06143	—
599-06144	6	400	—	—	29 293-06144	—
Close-off psi — High-temperature Range is 337° F max. (170° C)						
599-06120	2-1/2	63	38 275-06120	153 290-06120	—	38 267-06120
599-06121	3	100	25 275-06121	101 290-06121	—	25 267-06121
599-06122	4	160	—	—	65 293-06122	—
599-06123	5	250	—	—	42 293-06123	—
599-06124	6	400	—	—	29 293-06124	—
Normally Closed						
Close-off psi — Standard-temperature Range 20° F to 250° F (-7° C to 120° C)						
599-06150	2-1/2	63	34 275-06150	97 290-06150	—	34 267-06150
599-06151	3	100	22 275-06151	63 290-06151	—	22 267-06151
599-06152	4	160	—	—	39 293-06152	—
599-06153	5	250	—	—	25 293-06153	—
599-06154	6	400	—	—	17 293-06154	—
Close-off psi — High-temperature Range is 337° F max. (170° C)						
599-06130	2-1/2	63	34 275-06130	97 290-06130	—	34 267-06130
599-06131	3	100	22 275-06131	63 290-06131	—	22 267-06131
599-06132	4	160	—	—	39 293-06132	—
599-06133	5	250	—	—	25 293-06133	—
599-06134	6	400	—	—	17 293-06134	—

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.

A-53

Valves