

Three-Way Flanged **Globe** Valve Assemblies

ANSI Class 125

Electronic Spring Return or Non-Spring Return Actuators

- Mixing
- Bronze and Stainless Steel Trim



Mixing Flanged 2-1/2 to 6" 			Spring Return Actuator					
3-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	Floating 3P 	Floating 3P 	Floating 3P 	0-10 Vdc 4-20 mA 	0-10 Vdc 4-20 mA 	0-10 Vdc 4-20 mA 
			SKD82.51U	SKB82.51U	SKC82.61U	SKD62U	SKB62U	SKC62U
			Close-off psi — Bronze Trim					
599-06160	2-1/2	63	34 276-06160	97 289-06160	—	34 274-06160	97 291-06160	—
599-06161	3	100	22 276-06161	63 289-06161	—	22 274-06161	63 291-06161	—
599-06162	4	160	—	—	39 292-06162	—	—	39 294-06162
599-06163	5	250	—	—	25 292-06163	—	—	25 294-06163
599-06164	6	400	—	—	17 292-06164	—	—	17 294-06164
			Close-off psi — Stainless Steel Trim					
599-06165	2-1/2	63	34 276-06165	97 289-06165	—	34 274-06165	97 291-06165	—
599-06166	3	100	22 276-06166	63 289-06166	—	22 274-06166	63 291-06166	—
599-06167	4	160	—	—	39 292-06167	—	—	39 294-06167
599-06168	5	250	—	—	25 292-06168	—	—	25 294-06168
599-06169	6	400	—	—	17 292-06169	—	—	17 294-06169

Table Notes:

Part numbers in red indicate complete assemblies. Black numbers indicate close-off psi.

Values are for the NC upper port. For NO lower port values, refer to Engineering Section G.

Mixing Flanged 2-1/2 to 6" 			Non-Spring Return Actuator			
3-Way Valve Body Part No.	Valve Size in.	Flow Rate Cv	Floating 3P 	Floating 3P 	Floating 3P 	0-10 Vdc 4-20 mA  NEW!
			SKD82.50U	SKB82.50U	SKC82.60U	SKD60U
			Close-off psi — Bronze Trim			
599-06160	2-1/2	63	34 275-06160	97 290-06160	—	34 267-06160
599-06161	3	100	22 275-06161	63 290-06161	—	22 267-06161
599-06162	4	160	—	—	39 293-06162	—
599-06163	5	250	—	—	25 293-06163	—
599-06164	6	400	—	—	17 293-06164	—
			Close-off psi — Stainless Steel Trim			
599-06165	2-1/2	63	34 275-06165	97 290-06165	—	34 267-06165
599-06166	3	100	22 275-06166	63 290-06166	—	22 267-06166
599-06167	4	160	—	—	39 293-06167	—
599-06168	5	250	—	—	25 293-06168	—
599-06169	6	400	—	—	17 293-06169	—

Table Notes:

Part numbers in red indicate complete assemblies.

Black numbers indicate close-off psi.

Values are for the NC upper port. For NO lower port values, refer to Engineering, Section G.