data sheet

niagara supervisor

PRODUCT DEFINITION

The Niagara 4 Supervisor is an IoT (Internet of Things) software platform used in server-class applications. It makes managing all buildings at an enterprise level possible, giving facilities managers the ability to quickly respond to problems and insights to optimize their system.

The Niagara 4 Supervisor allows multiple Niagara-based JACE[®] controllers, along with other IP-based controllers and field devices, to be networked together. It serves real-time graphical information to standard Web-browser clients and provides server-level functions. These functions include centralized data logging/trending, archiving to external databases, alarming, dashboarding, system navigation, master scheduling, database management, and integration with other enterprise software applications through an XML interface (oBIX standard). Also, it provides a comprehensive graphical engineering toolset for application development.

ORDERING INFORMATION

Part number	Description
S-N4-0	No Niagara network – Devices only (18mo SMA req)
SUP-O-SMA-INIT	18mo initial SMA (3YR or 5YR can be substituted)
S-N4-1	1 Niagara network connection (18mo SMA req)
SUP-1-SMA-INIT	18mo initial SMA (3YR or 5YR can be substituted)
S-N4-2	2 Niagara network connections (18mo SMA req)
SUP-2-SMA-INIT	18mo initial SMA (3YR or 5YR can be substituted)
S-N4-3	3 Niagara network connections (18mo SMA req)
SUP-3-SMA-INIT	18mo initial SMA (3YR or 5YR can be substituted)
S-N4-10	10 Niagara network connections (18mo SMA req)
SUP-10-SMA-INIT	18mo initial SMA (3YR or 5YR can be substituted)
S-N4-100	100 Niagara network connections (18mo SMA req)
SUP-100-SMA-INIT	18mo initial SMA (3YR or 5YR can be substituted)
S-N4-UNL	Unlimited Niagara network connections (18mo SMA req)
SUP-UNL-SMA-INIT	18mo initial SMA (3YR or 5YR can be substituted)
SUP-DEMO	Niagara 4 Supervisor demo
S-N4-UP-1	Adds one additional Niagara connection to Niagara 4 Supervisor
S-N4-UP-100	Upgrades small Niagara 4 Supervisor to 100 Niagara connections
S-N4-UP-UNL	Upgrades Niagara 4 Supervisor 100 to unlimited Niagara connections
SUP-DEVICE-10	Adds 10 Non-Niagara IP Devices to a Niagara 4 Supervisor
SUP-DEVICE-25	Adds 25 Non-Niagara IP Devices to a Niagara 4 Supervisor
SUP-DEVICE-50	Adds 50 Non-Niagara IP Devices to a Niagara 4 Supervisor
SUP-DEVICE-100	Adds 100 Non-Niagara IP Devices to a Niagara 4 Supervisor
SUP-DEVICE-200	Adds 200 Non-Niagara IP Devices to a Niagara 4 Supervisor
SUP-AX	Enables a Niagara 4 Supervisor to run Niagara AX (v3.8)
SUP-[0-UNL]-SMA-[1,3,5]YR	Supervisor [0-UNL] Maintenance - [1,3,5] YR extensions

"If Maintenance coverage is not purchased for any period, the price of Maintenance for the next period for which it is purchased will be (i) the Maintenance fee for the period(s) for which Maintenance was not purchased, up to a maximum of 5 years; and (ii) the Maintenance fee for the next year.

KEY ADVANTAGES

- Centralized system management
- Quickly navigate to individual buildings using tags to diagnose problems
- Compare data between buildings
- Export system data to external databases
- Integrate BAS to other enterprise applications
- Integrate to other applications, such as work order management, analytics, etc.
- Single tool used to program JACE controllers and Supervisor
- Remotely back up JACE applications to Supervisor
- Batch provisioning of JACE firmware upgrades from Supervisor
- Robust built-in analytic capabilities supported by standard Niagara components and visualizations
- Compatibility with VYKON Integrated Analytics 2.0, adding data source, functional and mathematical programming blocks to enable sophisticated analytic algorithms



SUPPORTED DRIVERS

Many open protocol IP drivers are included with Niagara 4. Others can be purchased separately à la carte. For an up-to-date list of supported drivers, visit our resource library on vykon.com.

COMPATIBILITY

In any given Niagara system, the Niagara Supervisor must be running the highest version of any Niagara instance in the architecture.

When connecting to JACEs that are running older versions of Niagara, these compatibility guidelines apply:

- Niagara AX: Niagara 4 Supervisors can connect to JACEs running Niagara AX versions 3.6u4, 3.7u1, 3.8R and higher.
- R2: Niagara AX and Niagara 4 Supervisors can connect to JACEs running R2 through the oBIX XML interface only. oBIX is included in all Niagara AX and Niagara 4 Supervisors as a means of integrating Niagara-based Release 2 (R2) JACEs. With Niagara Release 2.3.522 or higher, the oBIX driver can be added to expose all data points, schedules, trends and alarms to a Niagara AX or Niagara 4 system. This oBIX driver is both a client and a server.

PLATFORM REQUIREMENTS FOR NIAGARA 4.2

Niagara 4 Supervisors may run acceptably on lower-rated platforms, or may even require more powerful platforms, depending on the application, number of data points integrated, data poll rate, number of concurrent users, performance expectations, etc.

- **Processor:** Intel[®] Xeon[®] CPU E5-2640 x64 (or better), compatible with dual- and quad-core processors
- Operating System: Windows 10, 64-bit Windows 8.1 Enterprise, 2012 R2 Standard, RHEL-7
- Memory: 1 GB minimum, 4 GB or more recommended for larger systems
- Hard Drive: 4 GB minimum, more recommended depending on archiving requirements
- **Display:** Video card and monitor capable of displaying 1024 x 768 pixel resolution or greater
- Network Support: Ethernet adapter (10/100 Mb with RJ-45 connector)
- Connectivity: Full-time high-speed ISP connection recommended for remote site access (i.e., T1, ADSL, cable modem) and IPv6 compliant

Platform requirements for older versions of Niagara Supervisors are included in the Release Notes for each particular version.

SPECIFICATIONS

HTML5 and Java-enabled user interface (UI); JavaScript data interface library included (BajaScript)

Supports an unlimited number of users over the Internet / intranet with a standard Web browser (depending on the host PC resources)

Optional enterprise-level data archival using SQL, MySQL or Oracle databases and HTTP/HTML/XML, CSV or text formats

"Audit Trail" of database changes, database storage and backup, global time functions, calendar, central scheduling, control and energy management routines

Sophisticated alarm processing and routing, including email alarm acknowledging

Access to alarms, logs, graphics, schedules and configuration data with a standard Web browser

Niagara follows industry best practices for cyber security, with support for features such as strong hashed passwords, TLSv1 for secure communications and certificate management tools for authentication

HTML-based help system that includes comprehensive online system documentation

Supports multiple Niagara-based stations connected to a local Ethernet network, or the Internet

Provides online/offline use of the Niagara Framework® Workbench AX graphical configuration tool and a comprehensive Java Object Library

Optional direct Ethernet-based driver support for most Open IP field bus protocols (see supported drivers document)

To learn more about how to purchase, install and start using the Niagara 4 Supervisor, contact your VYKON partner. The global community of certified Niagara professionals can serve your unique business needs across any industry or geographic region.



vykon.com

Copyright © 2016 Tridium Inc. All rights reserved. Intel and Xeon are trademarks of Intel Corporation in the U.S. and/or other countries.

Information and/or specifications published here are current as of the date of publication of this document. Tridium, Inc. reserves the right to change or modify specifications without prior notice. The latest product specifications can be found by contacting our corporate headquarters, Richmond, Virginia. Products or features contained herein may be covered by one or more U.S. or foreign patents. This document may be copied only as expressly authorized by Tridium in writing. It may not otherwise, in whole or in part, be copied, photocopied, preproduced, translated, or reduced to any electronic medium or machine-readable form.